

Internet Engineering Task Force (IETF)
Request for Comments: 5662
Category: Standards Track
ISSN: 2070-1721

S. Shepler, Ed.
Storspeed, Inc.
M. Eisler, Ed.
D. Noveck, Ed.
NetApp
January 2010

Network File System (NFS) Version 4 Minor Version 1
External Data Representation Standard (XDR) Description

Abstract

This document provides the External Data Representation Standard (XDR) description for Network File System version 4 (NFSv4) minor version 1.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc5662>.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
1.1. Requirements Language	2
1.2. Code Components Licensing Notice	2
2. XDR Description of NFSv4.1	2
3. Security Considerations	72
4. IANA Considerations	72
5. Normative References	72
Appendix A. Acknowledgments	73

1. Introduction

This document provides the External Data Representation Standard (XDR) description for Network File System version 4 (NFSv4) minor version 1.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [1].

1.2. Code Components Licensing Notice

The XDR description and scripts for extracting the XDR description are Code Components as described in Section 4 of "Legal Provisions Relating to IETF Documents" [2].

2. XDR Description of NFSv4.1

This document contains the XDR ([3]) description of NFSv4.1 protocol ([4]). In order to facilitate implementations that support both NFSv4.0 and NFSv4.1, the description includes operations and other features of NFSv4.0 that do not apply to NFSv4.1.

The XDR description is provided in this document in a way that makes it simple for the reader to extract into ready-to-compile form. The reader can feed this document in the following shell script to produce the machine readable XDR description of NFSv4.1:

<CODE BEGINS>

```
#!/bin/sh
grep '^ *////' | sed 's?^ *//// ??' | sed 's?^ *////$??'
```

<CODE ENDS>

That is, if the above script is stored in a file called "extract.sh", and this document is in a file called "spec.txt", then the reader can do:

<CODE BEGINS>

```
sh extract.sh < spec.txt > nfs4_prot.x
```

<CODE ENDS>

The effect of the script is to remove leading white space from each line, plus a sentinel sequence of "///".

The XDR description, with the sentinel sequence follows:

<CODE BEGINS>

```
/// /*
/// * Copyright (c) 2010 IETF Trust and the persons identified
/// * as the document authors. All rights reserved.
/// *
/// * The document authors are identified in RFC 3530 and
/// * RFC 5661.
/// *
/// * Redistribution and use in source and binary forms, with
/// * or without modification, are permitted provided that the
/// * following conditions are met:
/// *
/// * - Redistributions of source code must retain the above
/// *   copyright notice, this list of conditions and the
/// *   following disclaimer.
/// *
/// * - Redistributions in binary form must reproduce the above
/// *   copyright notice, this list of conditions and the
/// *   following disclaimer in the documentation and/or other
/// *   materials provided with the distribution.
/// *
/// * - Neither the name of Internet Society, IETF or IETF
/// *   Trust, nor the names of specific contributors, may be
/// *   used to endorse or promote products derived from this
/// *   software without specific prior written permission.
/// *
/// * THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS
/// * AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED
/// * WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
/// * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
/// * FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO
/// * EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
/// * LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
/// * EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
/// * NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
/// * SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
/// * INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
/// * LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
/// * OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING
/// * IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
/// * ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
/// */
```

```
/// /*
/// * This code was derived from RFC 3530. Please
/// * reproduce this note if possible.
/// *
/// * This code was derived from RFC 5661. Please
/// * reproduce this note if possible.
/// *
/// * This file was machine generated from RFC 5662.
/// */
/// /*
/// *      nfs4_prot.x
/// */
///
/// #ifndef _AUTH_SYS_DEFINE_FOR_NFSv41
/// #define _AUTH_SYS_DEFINE_FOR_NFSv41
/// #include <rpc/auth_sys.h>
/// #typedef struct authsys_parms authsys_parms;
/// #endif /* _AUTH_SYS_DEFINE_FOR_NFSv41 */
///
/// /*
/// * Basic typedefs for RFC 1832 data type definitions
/// */
///
/// /*
/// * typedef int                int32_t;
/// * typedef unsigned int      uint32_t;
/// * typedef hyper              int64_t;
/// * typedef unsigned hyper    uint64_t;
/// */
///
/// /*
/// * Sizes
/// */
///
/// const NFS4_FHSIZE                = 128;
/// const NFS4_VERIFIER_SIZE         = 8;
/// const NFS4_OPAQUE_LIMIT          = 1024;
/// const NFS4_SESSIONID_SIZE       = 16;
///
/// const NFS4_INT64_MAX              = 0x7fffffffffffffff;
/// const NFS4_UINT64_MAX             = 0xfffffffffffffff;
/// const NFS4_INT32_MAX              = 0x7fffffff;
/// const NFS4_UINT32_MAX             = 0xffffffff;
///
/// const NFS4_MAXFILELEN            = 0xfffffffffffffff;
/// const NFS4_MAXFILEOFF            = 0xfffffffffffffff;
///
/// /*
```

```

/// * File types
/// */
/// enum nfs_ftype4 {
///     NF4REG = 1,      /* Regular File */
///     NF4DIR = 2,      /* Directory */
///     NF4BLK = 3,      /* Special File - block device */
///     NF4CHR = 4,      /* Special File - character device */
///     NF4LNK = 5,      /* Symbolic Link */
///     NF4SOCK = 6,     /* Special File - socket */
///     NF4FIFO = 7,     /* Special File - fifo */
///     NF4ATTRDIR
///     = 8,             /* Attribute Directory */
///     NF4NAMEDATTR
///     = 9              /* Named Attribute */
/// };
///
/// /*
/// * Error status
/// */
/// enum nfsstat4 {
///     NFS4_OK = 0,      /* everything is okay */
///     NFS4ERR_PERM = 1, /* caller not privileged */
///     NFS4ERR_NOENT = 2, /* no such file/directory */
///     NFS4ERR_IO = 5,   /* hard I/O error */
///     NFS4ERR_NXIO = 6, /* no such device */
///     NFS4ERR_ACCESS = 13, /* access denied */
///     NFS4ERR_EXIST = 17, /* file already exists */
///     NFS4ERR_XDEV = 18, /* different filesystems */
///
///     /*
///     * Please do not allocate value 19; it was used in NFSv3
///     * and we do not want a value in NFSv3 to have a different
///     * meaning in NFSv4.x.
///     */
///
///     NFS4ERR_NOTDIR = 20, /* should be a directory */
///     NFS4ERR_ISDIR = 21, /* should not be directory */
///     NFS4ERR_INVALID = 22, /* invalid argument */
///     NFS4ERR_FBIG = 27, /* file exceeds server max */
///     NFS4ERR_NOSPC = 28, /* no space on filesystem */
///     NFS4ERR_ROFS = 30, /* read-only filesystem */
///     NFS4ERR_MLINK = 31, /* too many hard links */
///     NFS4ERR_NAMETOOLONG = 63, /* name exceeds server max */
///     NFS4ERR_NOTEMPTY = 66, /* directory not empty */
///     NFS4ERR_DQUOT = 69, /* hard quota limit reached */
///     NFS4ERR_STALE = 70, /* file no longer exists */
///     NFS4ERR_BADHANDLE = 10001, /* Illegal filehandle */
///     NFS4ERR_BAD_COOKIE = 10003, /* READDIR cookie is stale */

```

```

/// NFS4ERR_NOTSUPP      = 10004,/* operation not supported */
/// NFS4ERR_TOOSMALL    = 10005,/* response limit exceeded */
/// NFS4ERR_SERVERFAULT = 10006,/* undefined server error */
/// NFS4ERR_BADTYPE     = 10007,/* type invalid for CREATE */
/// NFS4ERR_DELAY       = 10008,/* file "busy" - retry */
/// NFS4ERR_SAME        = 10009,/* nverify says attrs same */
/// NFS4ERR_DENIED      = 10010,/* lock unavailable */
/// NFS4ERR_EXPIRED     = 10011,/* lock lease expired */
/// NFS4ERR_LOCKED      = 10012,/* I/O failed due to lock */
/// NFS4ERR_GRACE       = 10013,/* in grace period */
/// NFS4ERR_FHEXPIRED   = 10014,/* filehandle expired */
/// NFS4ERR_SHARE_DENIED = 10015,/* share reserve denied */
/// NFS4ERR_WRONGSEC    = 10016,/* wrong security flavor */
/// NFS4ERR_CLID_INUSE  = 10017,/* clientid in use */
///
/// /* NFS4ERR_RESOURCE is not a valid error in NFSv4.1 */
/// NFS4ERR_RESOURCE    = 10018,/* resource exhaustion */
///
/// NFS4ERR_MOVED       = 10019,/* filesystem relocated */
/// NFS4ERR_NOFILEHANDLE = 10020,/* current FH is not set */
/// NFS4ERR_MINOR_VERS_MISMATCH= 10021,/* minor vers not supp */
/// NFS4ERR_STALE_CLIENTID = 10022,/* server has rebooted */
/// NFS4ERR_STALE_STATEID = 10023,/* server has rebooted */
/// NFS4ERR_OLD_STATEID = 10024,/* state is out of sync */
/// NFS4ERR_BAD_STATEID = 10025,/* incorrect stateid */
/// NFS4ERR_BAD_SEQID   = 10026,/* request is out of seq. */
/// NFS4ERR_NOT_SAME    = 10027,/* verify - attrs not same */
/// NFS4ERR_LOCK_RANGE  = 10028,/* overlapping lock range */
/// NFS4ERR_SYMLINK     = 10029,/* should be file/directory*/
/// NFS4ERR_RESTOREFH   = 10030,/* no saved filehandle */
/// NFS4ERR_LEASE_MOVED = 10031,/* some filesystem moved */
/// NFS4ERR_ATTRNOTSUPP = 10032,/* recommended attr not supp*/
/// NFS4ERR_NO_GRACE    = 10033,/* reclaim outside of grace*/
/// NFS4ERR_RECLAIM_BAD = 10034,/* reclaim error at server */
/// NFS4ERR_RECLAIM_CONFLICT= 10035,/* conflict on reclaim */
/// NFS4ERR_BADXDR      = 10036,/* XDR decode failed */
/// NFS4ERR_LOCKS_HELD  = 10037,/* file locks held at CLOSE*/
/// NFS4ERR_OPENMODE    = 10038,/* conflict in OPEN and I/O*/
/// NFS4ERR_BADOWNER    = 10039,/* owner translation bad */
/// NFS4ERR_BADCHAR     = 10040,/* utf-8 char not supported*/
/// NFS4ERR_BADNAME     = 10041,/* name not supported */
/// NFS4ERR_BAD_RANGE   = 10042,/* lock range not supported*/
/// NFS4ERR_LOCK_NOTSUPP = 10043,/* no atomic up/downgrade */
/// NFS4ERR_OP_ILLEGAL  = 10044,/* undefined operation */
/// NFS4ERR_DEADLOCK    = 10045,/* file locking deadlock */
/// NFS4ERR_FILE_OPEN   = 10046,/* open file blocks op. */
/// NFS4ERR_ADMIN_REVOKED = 10047,/* lockowner state revoked */
/// NFS4ERR_CB_PATH_DOWN = 10048,/* callback path down */

```

```

///
/// /* NFSv4.1 errors start here. */
///
/// NFS4ERR_BADIOMODE          = 10049,
/// NFS4ERR_BADLAYOUT         = 10050,
/// NFS4ERR_BAD_SESSION_DIGEST = 10051,
/// NFS4ERR_BADSESSION        = 10052,
/// NFS4ERR_BADSLOT           = 10053,
/// NFS4ERR_COMPLETE_ALREADY  = 10054,
/// NFS4ERR_CONN_NOT_BOUND_TO_SESSION = 10055,
/// NFS4ERR_DELEG_ALREADY_WANTED = 10056,
/// NFS4ERR_BACK_CHAN_BUSY    = 10057, /*backchan reqs outstanding*/
/// NFS4ERR_LAYOUTTRYLATER    = 10058,
/// NFS4ERR_LAYOUTUNAVAILABLE = 10059,
/// NFS4ERR_NOMATCHING_LAYOUT = 10060,
/// NFS4ERR_RECALLCONFLICT    = 10061,
/// NFS4ERR_UNKNOWN_LAYOUTTYPE = 10062,
/// NFS4ERR_SEQ_MISORDERED    = 10063, /* unexpected seq.ID in req*/
/// NFS4ERR_SEQUENCE_POS      = 10064, /* [CB_]SEQ. op not 1st op */
/// NFS4ERR_REQ_TOO_BIG       = 10065, /* request too big          */
/// NFS4ERR_REP_TOO_BIG       = 10066, /* reply too big            */
/// NFS4ERR_REP_TOO_BIG_TO_CACHE = 10067, /* rep. not all cached*/
/// NFS4ERR_RETRY_UNCACHED_REP = 10068, /* retry & rep. uncached*/
/// NFS4ERR_UNSAFE_COMPOUND    = 10069, /* retry/recovery too hard */
/// NFS4ERR_TOO_MANY_OPS      = 10070, /*too many ops in [CB_]COMP*/
/// NFS4ERR_OP_NOT_IN_SESSION  = 10071, /* op needs [CB_]SEQ. op */
/// NFS4ERR_HASH_ALG_UNSUPP    = 10072, /* hash alg. not supp.    */
///                               /* Error 10073 is unused.  */
/// NFS4ERR_CLIENTID_BUSY     = 10074, /* clientid has state     */
/// NFS4ERR_PNFS_IO_HOLE      = 10075, /* IO to _SPARSE file hole */
/// NFS4ERR_SEQ_FALSE_RETRY   = 10076, /* Retry != original req.  */
/// NFS4ERR_BAD_HIGH_SLOT     = 10077, /* req has bad highest_slot*/
/// NFS4ERR_DEADSESSION       = 10078, /*new req sent to dead sess*/
/// NFS4ERR_ENCR_ALG_UNSUPP   = 10079, /* encr alg. not supp.    */
/// NFS4ERR_PNFS_NO_LAYOUT    = 10080, /* I/O without a layout   */
/// NFS4ERR_NOT_ONLY_OP       = 10081, /* addl ops not allowed   */
/// NFS4ERR_WRONG_CRED        = 10082, /* op done by wrong cred  */
/// NFS4ERR_WRONG_TYPE        = 10083, /* op on wrong type object */
/// NFS4ERR_DIRDELEG_UNAVAIL  = 10084, /* delegation not avail.  */
/// NFS4ERR_REJECT_DELEG      = 10085, /* cb rejected delegation  */
/// NFS4ERR_RETURNCONFLICT    = 10086, /* layout get before return*/
/// NFS4ERR_DELEG_REVOKED     = 10087 /* deleg./layout revoked  */
/// };
///
/// /*
///  * Basic data types
///  */
/// typedef opaque attrlist4<>;

```

```

/// typedef uint32_t      bitmap4<>;
/// typedef uint64_t      changeid4;
/// typedef uint64_t      clientid4;
/// typedef uint32_t      count4;
/// typedef uint64_t      length4;
/// typedef uint32_t      mode4;
/// typedef uint64_t      nfs_cookie4;
/// typedef opaque nfs_fh4<NFS4_FHSIZE>;
/// typedef uint64_t      offset4;
/// typedef uint32_t      qop4;
/// typedef opaque sec_oid4<>;
/// typedef uint32_t      sequenceid4;
/// typedef uint32_t      seqid4;
/// typedef opaque sessionid4[NFS4_SESSIONID_SIZE];
/// typedef uint32_t      slotid4;
/// typedef opaque utf8string<>;
/// typedef utf8string    utf8str_cis;
/// typedef utf8string    utf8str_cs;
/// typedef utf8string    utf8str_mixed;
/// typedef utf8str_cs    component4;
/// typedef utf8str_cs    linktext4;
/// typedef component4    pathname4<>;
/// typedef opaque verifier4[NFS4_VERIFIER_SIZE];
///
/// /*
///  * Timeval
///  */
/// struct nfstime4 {
///     int64_t      seconds;
///     uint32_t     nseconds;
/// };
///
/// enum time_how4 {
///     SET_TO_SERVER_TIME4 = 0,
///     SET_TO_CLIENT_TIME4 = 1
/// };
///
/// union settime4 switch (time_how4 set_it) {
///     case SET_TO_CLIENT_TIME4:
///         nfstime4      time;
///     default:
///         void;
/// };
///
///
/// typedef uint32_t nfs_lease4;
///
/// /*

```

```
/// * File attribute definitions
/// */
///
/// /*
/// * FSID structure for major/minor
/// */
/// struct fsid4 {
///     uint64_t      major;
///     uint64_t      minor;
/// };
///
/// /*
/// * Filesystem locations attribute
/// * for relocation/migration and
/// * related attributes.
/// */
/// struct change_policy4 {
///     uint64_t      cp_major;
///     uint64_t      cp_minor;
/// };
///
/// struct fs_location4 {
///     utf8str_cis   server<>;
///     pathname4     rootpath;
/// };
///
/// struct fs_locations4 {
///     pathname4     fs_root;
///     fs_location4  locations<>;
/// };
///
/// /*
/// * Various Access Control Entry definitions
/// */
///
/// /*
/// * Mask that indicates which
/// * Access Control Entries are supported.
/// * Values for the fattr4_aclsupport attribute.
/// */
/// const ACL4_SUPPORT_ALLOW_ACL    = 0x00000001;
/// const ACL4_SUPPORT_DENY_ACL     = 0x00000002;
/// const ACL4_SUPPORT_AUDIT_ACL    = 0x00000004;
/// const ACL4_SUPPORT_ALARM_ACL    = 0x00000008;
///
///
/// typedef uint32_t      acetype4;
///
```

```
///
/// /*
/// * acetype4 values, others can be added as needed.
/// */
/// const ACE4_ACCESS_ALLOWED_ACE_TYPE      = 0x00000000;
/// const ACE4_ACCESS_DENIED_ACE_TYPE      = 0x00000001;
/// const ACE4_SYSTEM_AUDIT_ACE_TYPE       = 0x00000002;
/// const ACE4_SYSTEM_ALARM_ACE_TYPE       = 0x00000003;
///
///
///
/// /*
/// * ACE flag
/// */
/// typedef uint32_t aceflag4;
///
///
/// /*
/// * ACE flag values
/// */
/// const ACE4_FILE_INHERIT_ACE             = 0x00000001;
/// const ACE4_DIRECTORY_INHERIT_ACE       = 0x00000002;
/// const ACE4_NO_PROPAGATE_INHERIT_ACE    = 0x00000004;
/// const ACE4_INHERIT_ONLY_ACE           = 0x00000008;
/// const ACE4_SUCCESSFUL_ACCESS_ACE_FLAG  = 0x00000010;
/// const ACE4_FAILED_ACCESS_ACE_FLAG     = 0x00000020;
/// const ACE4_IDENTIFIER_GROUP           = 0x00000040;
/// const ACE4_INHERITED_ACE              = 0x00000080;
///
///
///
/// /*
/// * ACE mask
/// */
/// typedef uint32_t          acemask4;
///
///
/// /*
/// * ACE mask values
/// */
/// const ACE4_READ_DATA                  = 0x00000001;
/// const ACE4_LIST_DIRECTORY              = 0x00000001;
/// const ACE4_WRITE_DATA                  = 0x00000002;
/// const ACE4_ADD_FILE                    = 0x00000002;
/// const ACE4_APPEND_DATA                 = 0x00000004;
/// const ACE4_ADD_SUBDIRECTORY            = 0x00000004;
/// const ACE4_READ_NAMED_ATTRS           = 0x00000008;
/// const ACE4_WRITE_NAMED_ATTRS          = 0x00000010;
```

```
/// const ACE4_EXECUTE           = 0x00000020;
/// const ACE4_DELETE_CHILD      = 0x00000040;
/// const ACE4_READ_ATTRIBUTES   = 0x00000080;
/// const ACE4_WRITE_ATTRIBUTES  = 0x00000100;
/// const ACE4_WRITE_RETENTION   = 0x00000200;
/// const ACE4_WRITE_RETENTION_HOLD = 0x00000400;
///
/// const ACE4_DELETE            = 0x00010000;
/// const ACE4_READ_ACL          = 0x00020000;
/// const ACE4_WRITE_ACL         = 0x00040000;
/// const ACE4_WRITE_OWNER       = 0x00080000;
/// const ACE4_SYNCHRONIZE       = 0x00100000;
///
///
/// /*
///  * ACE4_GENERIC_READ -- defined as combination of
///  *   ACE4_READ_ACL |
///  *   ACE4_READ_DATA |
///  *   ACE4_READ_ATTRIBUTES |
///  *   ACE4_SYNCHRONIZE
///  */
///
/// const ACE4_GENERIC_READ = 0x00120081;
///
/// /*
///  * ACE4_GENERIC_WRITE -- defined as combination of
///  *   ACE4_READ_ACL |
///  *   ACE4_WRITE_DATA |
///  *   ACE4_WRITE_ATTRIBUTES |
///  *   ACE4_WRITE_ACL |
///  *   ACE4_APPEND_DATA |
///  *   ACE4_SYNCHRONIZE
///  */
///
/// const ACE4_GENERIC_WRITE = 0x00160106;
///
///
/// /*
///  * ACE4_GENERIC_EXECUTE -- defined as combination of
///  *   ACE4_READ_ACL
///  *   ACE4_READ_ATTRIBUTES
///  *   ACE4_EXECUTE
///  *   ACE4_SYNCHRONIZE
///  */
///
/// const ACE4_GENERIC_EXECUTE = 0x001200A0;
///
///
/// /*
///  * Access Control Entry definition
```

```

/// */
/// struct nfsace4 {
///     acetype4         type;
///     aceflag4         flag;
///     acemask4         access_mask;
///     utf8str_mixed    who;
/// };
///
///
/// /*
///  * ACL flag
///  */
///
/// typedef uint32_t aclflag4;
///
/// /*
///  * ACL flag values
///  */
/// const ACL4_AUTO_INHERIT      = 0x00000001;
/// const ACL4_PROTECTED         = 0x00000002;
/// const ACL4_DEFAULTED         = 0x00000004;
///
///
/// /*
///  * Version 4.1 Access Control List definition
///  */
/// struct nfsacl41 {
///     aclflag4         na41_flag;
///     nfsace4          na41_aces<>;
/// };
///
///
/// /*
///  * Field definitions for the fattr4_mode
///  * and fattr4_mode_set_masked attributes.
///  */
/// const MODE4_SUID = 0x800; /* set user id on execution */
/// const MODE4_SGID = 0x400; /* set group id on execution */
/// const MODE4_SVTX = 0x200; /* save text even after use */
/// const MODE4_RUSR = 0x100; /* read permission: owner */
/// const MODE4_WUSR = 0x080; /* write permission: owner */
/// const MODE4_XUSR = 0x040; /* execute permission: owner */
/// const MODE4_RGRP = 0x020; /* read permission: group */
/// const MODE4_WGRP = 0x010; /* write permission: group */
/// const MODE4_XGRP = 0x008; /* execute permission: group */
/// const MODE4_ROTH = 0x004; /* read permission: other */
/// const MODE4_WOTH = 0x002; /* write permission: other */
/// const MODE4_XOTH = 0x001; /* execute permission: other */

```

```

///
///
/// /*
///  * Masked mode for the mode_set_masked attribute.
///  */
/// struct mode_masked4 {
///     mode4 mm_value_to_set; /* Values of bits
///                             to set or reset
///                             in mode. */
///
///     mode4 mm_mask_bits;    /* Mask of bits to
///                             set or reset
///                             in mode. */
/// };
///
/// /*
///  * Special data/attribute associated with
///  * file types NF4BLK and NF4CHR.
///  */
/// struct specdata4 {
///     uint32_t specdata1; /* major device number */
///     uint32_t specdata2; /* minor device number */
/// };
///
/// /*
///  * Values for fattr4_fh_expire_type
///  */
/// const    FH4_PERSISTENT           = 0x00000000;
/// const    FH4_NOEXPIRE_WITH_OPEN  = 0x00000001;
/// const    FH4_VOLATILE_ANY         = 0x00000002;
/// const    FH4_VOL_MIGRATION        = 0x00000004;
/// const    FH4_VOL_RENAME           = 0x00000008;
///
///
/// struct netaddr4 {
///     /* see struct rpcb in RFC 1833 */
///     string na_r_netid<>; /* network id */
///     string na_r_addr<>; /* universal address */
/// };
///
/// /*
///  * data structures new to NFSv4.1
///  */
///
/// struct nfs_impl_id4 {
///     utf8str_cis  nii_domain;
///     utf8str_cs   nii_name;
///     nfstime4     nii_date;

```

```

/// };
///
///
/// /*
///  * Stateid
///  */
/// struct stateid4 {
///     uint32_t      seqid;
///     opaque        other[12];
/// };
///
/// enum layouttype4 {
///     LAYOUT4_NFSV4_1_FILES      = 0x1,
///     LAYOUT4 OSD2_OBJECTS      = 0x2,
///     LAYOUT4_BLOCK_VOLUME      = 0x3
/// };
///
/// struct layout_content4 {
///     layouttype4 loc_type;
///     opaque      loc_body<>;
/// };
///
///
///
/// /*
///  * LAYOUT4 OSD2_OBJECTS loc_body description
///  * is in a separate .x file
///  */
///
/// /*
///  * LAYOUT4_BLOCK_VOLUME loc_body description
///  * is in a separate .x file
///  */
///
/// struct layouthint4 {
///     layouttype4      loh_type;
///     opaque           loh_body<>;
/// };
///
/// enum layoutiomode4 {
///     LAYOUTIOMODE4_READ      = 1,
///     LAYOUTIOMODE4_RW       = 2,
///     LAYOUTIOMODE4_ANY       = 3
/// };
///
/// struct layout4 {
///     offset4          lo_offset;
///     length4         lo_length;
///     layoutiomode4    lo_iomode;

```

```

    ///         layout_content4         lo_content;
    /// };
    ///
    /// const NFS4_DEVICEID4_SIZE = 16;
    ///
    /// typedef opaque deviceid4[NFS4_DEVICEID4_SIZE];
    ///
    /// struct device_addr4 {
    ///         layouttype4         da_layout_type;
    ///         opaque             da_addr_body<>;
    /// };
    ///
    ///
    /// struct layoutupdate4 {
    ///         layouttype4         lou_type;
    ///         opaque             lou_body<>;
    /// };
    ///
    /// %
    /// /* Constants used for LAYOUTRETURN and CB_LAYOUTRECALL */
    /// const LAYOUT4_RET_REC_FILE         = 1;
    /// const LAYOUT4_RET_REC_FSID        = 2;
    /// const LAYOUT4_RET_REC_ALL         = 3;
    /// %
    /// enum layoutreturn_type4 {
    ///         LAYOUTRETURN4_FILE = LAYOUT4_RET_REC_FILE,
    ///         LAYOUTRETURN4_FSID = LAYOUT4_RET_REC_FSID,
    ///         LAYOUTRETURN4_ALL  = LAYOUT4_RET_REC_ALL
    /// };
    ///
    /// struct layoutreturn_file4 {
    ///         offset4         lrf_offset;
    ///         length4        lrf_length;
    ///         stateid4       lrf_stateid;
    /// % /* layouttype4 specific data */
    ///         opaque         lrf_body<>;
    /// };
    ///
    /// union layoutreturn4 switch(layoutreturn_type4 lr_returntype) {
    ///         case LAYOUTRETURN4_FILE:
    ///                 layoutreturn_file4         lr_layout;
    ///         default:
    ///                 void;
    /// };
    /// %
    ///
    /// enum fs4_status_type {
    ///         STATUS4_FIXED = 1,

```

```

///     STATUS4_UPDATED = 2,
///     STATUS4_VERSIONED = 3,
///     STATUS4_WRITABLE = 4,
///     STATUS4_REFERRAL = 5
/// };
///
/// struct fs4_status {
///     bool                fss_absent;
///     fs4_status_type    fss_type;
///     utf8str_cs         fss_source;
///     utf8str_cs         fss_current;
///     int32_t            fss_age;
///     nfstime4           fss_version;
/// };
///
///
/// const TH4_READ_SIZE      = 0;
/// const TH4_WRITE_SIZE     = 1;
/// const TH4_READ_IOSIZE   = 2;
/// const TH4_WRITE_IOSIZE  = 3;
///
/// typedef length4 threshold4_read_size;
/// typedef length4 threshold4_write_size;
/// typedef length4 threshold4_read_iosize;
/// typedef length4 threshold4_write_iosize;
///
/// struct threshold_item4 {
///     layouttype4        thi_layout_type;
///     bitmap4            thi_hintset;
///     opaque              thi_hintlist<>;
/// };
///
/// struct mdsthreshold4 {
///     threshold_item4    mth_hints<>;
/// };
///
/// const RET4_DURATION_INFINITE = 0xffffffffffffffff;
/// struct retention_get4 {
///     uint64_t           rg_duration;
///     nfstime4           rg_begin_time<1>;
/// };
///
/// struct retention_set4 {
///     bool                rs_enable;
///     uint64_t            rs_duration<1>;
/// };
///
/// const FSCHARSET_CAP4_CONTAINS_NON_UTF8 = 0x1;

```

```
/// const FSCHARSET_CAP4_ALLOWS_ONLY_UTF8 = 0x2;
///
/// typedef uint32_t      fs_charset_cap4;
///
///
/// /*
///  * NFSv4.1 attributes
///  */
/// typedef bitmap4      fattr4_supported_attrs;
/// typedef nfs_ftype4   fattr4_type;
/// typedef uint32_t     fattr4_fh_expire_type;
/// typedef changeid4   fattr4_change;
/// typedef uint64_t     fattr4_size;
/// typedef bool        fattr4_link_support;
/// typedef bool        fattr4_symlink_support;
/// typedef bool        fattr4_named_attr;
/// typedef fsid4       fattr4_fsid;
/// typedef bool        fattr4_unique_handles;
/// typedef nfs_lease4  fattr4_lease_time;
/// typedef nfsstat4    fattr4_rdattrib_error;
/// typedef nfsace4     fattr4_acl<>;
/// typedef uint32_t    fattr4_aclsupport;
/// typedef bool        fattr4_archive;
/// typedef bool        fattr4_cansettime;
/// typedef bool        fattr4_case_insensitive;
/// typedef bool        fattr4_case_preserving;
/// typedef bool        fattr4_chown_restricted;
/// typedef uint64_t    fattr4_fileid;
/// typedef uint64_t    fattr4_files_avail;
/// typedef nfs_fh4     fattr4_filehandle;
/// typedef uint64_t    fattr4_files_free;
/// typedef uint64_t    fattr4_files_total;
/// typedef fs_locations4 fattr4_fs_locations;
/// typedef bool        fattr4_hidden;
/// typedef bool        fattr4_homogeneous;
/// typedef uint64_t    fattr4_maxfilesize;
/// typedef uint32_t    fattr4_maxlink;
/// typedef uint32_t    fattr4_maxname;
/// typedef uint64_t    fattr4_maxread;
/// typedef uint64_t    fattr4_maxwrite;
/// typedef utf8str_cs  fattr4_mimetype;
/// typedef mode4       fattr4_mode;
/// typedef mode_masked4 fattr4_mode_set_masked;
/// typedef uint64_t    fattr4_mounted_on_fileid;
/// typedef bool        fattr4_no_trunc;
/// typedef uint32_t    fattr4_numlinks;
/// typedef utf8str_mixed fattr4_owner;
/// typedef utf8str_mixed fattr4_owner_group;
```

```

/// typedef uint64_t      fattr4_quota_avail_hard;
/// typedef uint64_t      fattr4_quota_avail_soft;
/// typedef uint64_t      fattr4_quota_used;
/// typedef specdata4     fattr4_rawdev;
/// typedef uint64_t      fattr4_space_avail;
/// typedef uint64_t      fattr4_space_free;
/// typedef uint64_t      fattr4_space_total;
/// typedef uint64_t      fattr4_space_used;
/// typedef bool          fattr4_system;
/// typedef nfstime4      fattr4_time_access;
/// typedef settime4      fattr4_time_access_set;
/// typedef nfstime4      fattr4_time_backup;
/// typedef nfstime4      fattr4_time_create;
/// typedef nfstime4      fattr4_time_delta;
/// typedef nfstime4      fattr4_time_metadata;
/// typedef nfstime4      fattr4_time_modify;
/// typedef settime4      fattr4_time_modify_set;
/// /*
///  * attributes new to NFSv4.1
///  */
/// typedef bitmap4       fattr4_suppattr_exclcreat;
/// typedef nfstime4      fattr4_dir_notif_delay;
/// typedef nfstime4      fattr4_dirent_notif_delay;
/// typedef layouttype4   fattr4_fs_layout_types<>;
/// typedef fs4_status     fattr4_fs_status;
/// typedef fs_charset_cap4 fattr4_fs_charset_cap;
/// typedef uint32_t       fattr4_layout_alignment;
/// typedef uint32_t       fattr4_layout_blksize;
/// typedef layouthint4    fattr4_layout_hint;
/// typedef layouttype4   fattr4_layout_types<>;
/// typedef mdsthreshold4  fattr4_mdsthreshold;
/// typedef retention_get4 fattr4_retention_get;
/// typedef retention_set4 fattr4_retention_set;
/// typedef retention_get4 fattr4_retentevt_get;
/// typedef retention_set4 fattr4_retentevt_set;
/// typedef uint64_t       fattr4_retention_hold;
/// typedef nfsacl41       fattr4_dacl;
/// typedef nfsacl41       fattr4_sacl;
/// typedef change_policy4 fattr4_change_policy;
///
/// %/*
/// % * REQUIRED Attributes
/// % */
/// const FATTR4_SUPPORTED_ATTRS = 0;
/// const FATTR4_TYPE              = 1;
/// const FATTR4_FH_EXPIRE_TYPE    = 2;
/// const FATTR4_CHANGE            = 3;
/// const FATTR4_SIZE              = 4;

```

```
/// const FATTR4_LINK_SUPPORT      = 5;
/// const FATTR4_SYMLINK_SUPPORT   = 6;
/// const FATTR4_NAMED_ATTR        = 7;
/// const FATTR4_FSID              = 8;
/// const FATTR4_UNIQUE_HANDLES    = 9;
/// const FATTR4_LEASE_TIME        = 10;
/// const FATTR4_RDATTR_ERROR      = 11;
/// const FATTR4_FILEHANDLE        = 19;
/// /* new to NFSV4.1 */
/// const FATTR4_SUPPATR_EXCLCREAT = 75;
///
/// /*
///  * RECOMMENDED Attributes
///  */
/// const FATTR4_ACL                = 12;
/// const FATTR4_ACLSUPPORT         = 13;
/// const FATTR4_ARCHIVE            = 14;
/// const FATTR4_CANSETTIME         = 15;
/// const FATTR4_CASE_INSENSITIVE   = 16;
/// const FATTR4_CASE_PRESERVING    = 17;
/// const FATTR4_CHOWN_RESTRICTED   = 18;
/// const FATTR4_FILEID             = 20;
/// const FATTR4_FILES_AVAIL        = 21;
/// const FATTR4_FILES_FREE         = 22;
/// const FATTR4_FILES_TOTAL        = 23;
/// const FATTR4_FS_LOCATIONS       = 24;
/// const FATTR4_HIDDEN             = 25;
/// const FATTR4_HOMOGENEOUS        = 26;
/// const FATTR4_MAXFILESIZE        = 27;
/// const FATTR4_MAXLINK            = 28;
/// const FATTR4_MAXNAME            = 29;
/// const FATTR4_MAXREAD            = 30;
/// const FATTR4_MAXWRITE           = 31;
/// const FATTR4_MIMETYPE           = 32;
/// const FATTR4_MODE               = 33;
/// const FATTR4_NO_TRUNC           = 34;
/// const FATTR4_NUMLINKS           = 35;
/// const FATTR4_OWNER              = 36;
/// const FATTR4_OWNER_GROUP        = 37;
/// const FATTR4_QUOTA_AVAIL_HARD    = 38;
/// const FATTR4_QUOTA_AVAIL_SOFT   = 39;
/// const FATTR4_QUOTA_USED         = 40;
/// const FATTR4_RAWDEV             = 41;
/// const FATTR4_SPACE_AVAIL        = 42;
/// const FATTR4_SPACE_FREE         = 43;
/// const FATTR4_SPACE_TOTAL        = 44;
/// const FATTR4_SPACE_USED         = 45;
/// const FATTR4_SYSTEM             = 46;
```

```

/// const FATTR4_TIME_ACCESS      = 47;
/// const FATTR4_TIME_ACCESS_SET  = 48;
/// const FATTR4_TIME_BACKUP      = 49;
/// const FATTR4_TIME_CREATE      = 50;
/// const FATTR4_TIME_DELTA       = 51;
/// const FATTR4_TIME_METADATA    = 52;
/// const FATTR4_TIME_MODIFY      = 53;
/// const FATTR4_TIME_MODIFY_SET  = 54;
/// const FATTR4_MOUNTED_ON_FILEID = 55;
/// %
/// %/* new to NFSV4.1 */
/// %
/// const FATTR4_DIR_NOTIF_DELAY   = 56;
/// const FATTR4_DIRENT_NOTIF_DELAY = 57;
/// const FATTR4_DACL              = 58;
/// const FATTR4_SACL              = 59;
/// const FATTR4_CHANGE_POLICY     = 60;
/// const FATTR4_FS_STATUS         = 61;
/// const FATTR4_FS_LAYOUT_TYPES   = 62;
/// const FATTR4_LAYOUT_HINT       = 63;
/// const FATTR4_LAYOUT_TYPES     = 64;
/// const FATTR4_LAYOUT_BLKSIZE    = 65;
/// const FATTR4_LAYOUT_ALIGNMENT  = 66;
/// const FATTR4_FS_LOCATIONS_INFO = 67;
/// const FATTR4_MDSTHRESHOLD      = 68;
/// const FATTR4_RETENTION_GET     = 69;
/// const FATTR4_RETENTION_SET     = 70;
/// const FATTR4_RETENTEVTT_GET    = 71;
/// const FATTR4_RETENTEVTT_SET    = 72;
/// const FATTR4_RETENTION_HOLD    = 73;
/// const FATTR4_MODE_SET_MASKED   = 74;
/// const FATTR4_FS_CHARSET_CAP    = 76;
///
/// /*
///  * File attribute container
///  */
/// struct fattr4 {
///     bitmap4      attrmask;
///     attrlist4    attr_vals;
/// };
///
/// /*
///  * Change info for the client
///  */
/// struct change_info4 {
///     bool         atomic;
///     changeid4    before;
///     changeid4    after;

```

```

/// };
///
/// typedef netaddr4 clientaddr4;
///
/// /*
///  * Callback program info as provided by the client
///  */
/// struct cb_client4 {
///     uint32_t      cb_program;
///     netaddr4      cb_location;
/// };
///
/// /*
///  * NFSv4.0 Long Hand Client ID
///  */
/// struct nfs_client_id4 {
///     verifier4     verifier;
///     opaque         id<NFS4_OPAQUE_LIMIT>;
/// };
///
/// /*
///  * NFSv4.1 Client Owner (aka long hand client ID)
///  */
/// struct client_owner4 {
///     verifier4     co_verifier;
///     opaque         co_ownerid<NFS4_OPAQUE_LIMIT>;
/// };
///
/// /*
///  * NFSv4.1 server Owner
///  */
/// struct server_owner4 {
///     uint64_t      so_minor_id;
///     opaque         so_major_id<NFS4_OPAQUE_LIMIT>;
/// };
///
/// struct state_owner4 {
///     clientid4     clientid;
///     opaque         owner<NFS4_OPAQUE_LIMIT>;
/// };
///
/// typedef state_owner4 open_owner4;
/// typedef state_owner4 lock_owner4;
///
/// enum nfs_lock_type4 {

```

```

///      READ_LT      = 1,
///      WRITE_LT     = 2,
///      READW_LT     = 3,    /* blocking read */
///      WRITEW_LT    = 4    /* blocking write */
/// };
///
///
/// %
/// /* Input for computing subkeys */
/// enum ssv_subkey4 {
///     SSV4_SUBKEY_MIC_I2T      = 1,
///     SSV4_SUBKEY_MIC_T2I      = 2,
///     SSV4_SUBKEY_SEAL_I2T     = 3,
///     SSV4_SUBKEY_SEAL_T2I     = 4
/// };
/// %
///
/// %
/// /* Input for computing smt_hmac */
/// struct ssv_mic_plain_tkn4 {
///     uint32_t      smpt_ssv_seq;
///     opaque        smpt_orig_plain<>;
/// };
/// %
///
/// %
/// /* SSV GSS PerMsgToken token */
/// struct ssv_mic_tkn4 {
///     uint32_t      smt_ssv_seq;
///     opaque        smt_hmac<>;
/// };
/// %
///
/// %
/// /* Input for computing ssct_encr_data and ssct_hmac */
/// struct ssv_seal_plain_tkn4 {
///     opaque        sspt_confounder<>;
///     uint32_t      sspt_ssv_seq;
///     opaque        sspt_orig_plain<>;
///     opaque        sspt_pad<>;
/// };
/// %
///
/// %
/// /* SSV GSS SealedMessage token */
/// struct ssv_seal_cipher_tkn4 {
///     uint32_t      ssct_ssv_seq;
///     opaque        ssct_iv<>;

```

```

/// opaque      ssct_encr_data<>;
/// opaque      ssct_hmac<>;
/// };
/// %
///
/// /*
///  * Defines an individual server replica
///  */
/// struct fs_locations_server4 {
///     int32_t      fls_currency;
///     opaque       fls_info<>;
///     utf8str_cis  fls_server;
/// };
///
/// /*
///  * Byte indices of items within
///  * fls_info: flag fields, class numbers,
///  * bytes indicating ranks and orders.
///  */
/// const FSLI4BX_GFLAGS          = 0;
/// const FSLI4BX_TFLAGS         = 1;
///
/// const FSLI4BX_CLSIMUL        = 2;
/// const FSLI4BX_CLHANDLE       = 3;
/// const FSLI4BX_CLFILEID      = 4;
/// const FSLI4BX_CLWRITEVER    = 5;
/// const FSLI4BX_CLCHANGE      = 6;
/// const FSLI4BX_CLREADDIR     = 7;
///
/// const FSLI4BX_READRANK      = 8;
/// const FSLI4BX_WRITERANK     = 9;
/// const FSLI4BX_READORDER     = 10;
/// const FSLI4BX_WRITEORDER    = 11;
///
/// /*
///  * Bits defined within the general flag byte.
///  */
/// const FSLI4GF_WRITABLE      = 0x01;
/// const FSLI4GF_CUR_REQ       = 0x02;
/// const FSLI4GF_ABSENT        = 0x04;
/// const FSLI4GF_GOING         = 0x08;
/// const FSLI4GF_SPLIT         = 0x10;
///
/// /*
///  * Bits defined within the transport flag byte.
///  */
/// const FSLI4TF_RDMA          = 0x01;
///

```

```

/// /*
/// * Defines a set of replicas sharing
/// * a common value of the root path
/// * with in the corresponding
/// * single-server namespaces.
/// */
/// struct fs_locations_item4 {
///     fs_locations_server4    fli_entries<>;
///     pathname4                fli_rootpath;
/// };
///
/// /*
/// * Defines the overall structure of
/// * the fs_locations_info attribute.
/// */
/// struct fs_locations_info4 {
///     uint32_t                 fli_flags;
///     int32_t                  fli_valid_for;
///     pathname4                fli_fs_root;
///     fs_locations_item4      fli_items<>;
/// };
///
/// /*
/// * Flag bits in fli_flags.
/// */
/// const FSLI4IF_VAR_SUB      = 0x00000001;
///
/// typedef fs_locations_info4 fattr4_fs_locations_info;
///
/// const NFL4_UFLG_MASK       = 0x0000003F;
/// const NFL4_UFLG_DENSE      = 0x00000001;
/// const NFL4_UFLG_COMMIT_THRU_MDS = 0x00000002;
/// const NFL4_UFLG_STRIPE_UNIT_SIZE_MASK
///                             = 0xFFFFFFFFC0;
///
/// typedef uint32_t nfl_util4;
///
/// %
///
/// enum filelayout_hint_care4 {
///     NFLH4_CARE_DENSE          = NFL4_UFLG_DENSE,
///
///     NFLH4_CARE_COMMIT_THRU_MDS
///                             = NFL4_UFLG_COMMIT_THRU_MDS,
///
///     NFLH4_CARE_STRIPE_UNIT_SIZE
///                             = 0x00000040,
///

```

```

    ///          NFLH4_CARE_STRIPE_COUNT = 0x00000080
    /// };
    /// %
    /// /* Encoded in the loh_body field of data type layouthint4: */
    /// %
    /// struct nfsv4_1_file_layouthint4 {
    ///     uint32_t          nflh_care;
    ///     nfl_util4         nflh_util;
    ///     count4           nflh_stripe_count;
    /// };
    ///
    /// %
    /// %
    /// typedef netaddr4 multipath_list4<>;
    /// %
    /// /*
    /// % * Encoded in the da_addr_body field of
    /// % * data type device_addr4:
    /// % */
    /// struct nfsv4_1_file_layout_ds_addr4 {
    ///     uint32_t          nflda_stripe_indices<>;
    ///     multipath_list4  nflda_multipath_ds_list<>;
    /// };
    ///
    /// %
    /// %
    /// /*
    /// % * Encoded in the loc_body field of
    /// % * data type layout_content4:
    /// % */
    /// struct nfsv4_1_file_layout4 {
    ///     deviceid4        nfl_deviceid;
    ///     nfl_util4        nfl_util;
    ///     uint32_t         nfl_first_stripe_index;
    ///     offset4          nfl_pattern_offset;
    ///     nfs_fh4          nfl_fh_list<>;
    /// };
    ///
    /// %
    /// %
    /// /*
    /// % * Encoded in the lou_body field of data type layoutupdate4:
    /// % *      Nothing. lou_body is a zero length array of bytes.
    /// % */
    /// %
    ///

```

```

/// %/*
/// % * Encoded in the lrf_body field of
/// % * data type layoutreturn_file4:
/// % *      Nothing. lrf_body is a zero length array of bytes.
/// % */
/// %
///
///
/// const ACCESS4_READ          = 0x00000001;
/// const ACCESS4_LOOKUP        = 0x00000002;
/// const ACCESS4_MODIFY         = 0x00000004;
/// const ACCESS4_EXTEND         = 0x00000008;
/// const ACCESS4_DELETE         = 0x00000010;
/// const ACCESS4_EXECUTE        = 0x00000020;
///
/// struct ACCESS4args {
///     /* CURRENT_FH: object */
///     uint32_t      access;
/// };
///
/// struct ACCESS4resok {
///     uint32_t      supported;
///     uint32_t      access;
/// };
///
/// union ACCESS4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         ACCESS4resok      resok4;
///     default:
///         void;
/// };
///
/// struct CLOSE4args {
///     /* CURRENT_FH: object */
///     seqid4        seqid;
///     stateid4      open_stateid;
/// };
///
/// union CLOSE4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         stateid4      open_stateid;
///     default:
///         void;
/// };
///
/// struct COMMIT4args {
///     /* CURRENT_FH: file */
///     offset4       offset;

```

```

    ///         count4         count;
    /// };
    ///
    /// struct COMMIT4resok {
    ///         verifier4         writeverf;
    /// };
    ///
    /// union COMMIT4res switch (nfsstat4 status) {
    ///     case NFS4_OK:
    ///         COMMIT4resok     resok4;
    ///     default:
    ///         void;
    /// };
    ///
    /// union createtype4 switch (nfs_ftype4 type) {
    ///     case NF4LNK:
    ///         linktext4 linkdata;
    ///     case NF4BLK:
    ///     case NF4CHR:
    ///         specdata4 devdata;
    ///     case NF4SOCK:
    ///     case NF4FIFO:
    ///     case NF4DIR:
    ///         void;
    ///     default:
    ///         void; /* server should return NFS4ERR_BADTYPE */
    /// };
    ///
    /// struct CREATE4args {
    ///         /* CURRENT_FH: directory for creation */
    ///         createtype4     objtype;
    ///         component4     objname;
    ///         fattr4         createattrs;
    /// };
    ///
    /// struct CREATE4resok {
    ///         change_info4     cinfo;
    ///         bitmap4         attrset; /* attributes set */
    /// };
    ///
    /// union CREATE4res switch (nfsstat4 status) {
    ///     case NFS4_OK:
    ///         /* new CURRENTFH: created object */
    ///         CREATE4resok     resok4;
    ///     default:
    ///         void;
    /// };
    ///

```

```

/// struct DELEGPURGE4args {
///     clientid4      clientid;
/// };
///
/// struct DELEGPURGE4res {
///     nfsstat4       status;
/// };
///
/// struct DELEGRETURN4args {
///     /* CURRENT_FH: delegated object */
///     stateid4       deleg_stateid;
/// };
///
/// struct DELEGRETURN4res {
///     nfsstat4       status;
/// };
///
/// struct GETATTR4args {
///     /* CURRENT_FH: object */
///     bitmap4        attr_request;
/// };
///
/// struct GETATTR4resok {
///     fattr4         obj_attributes;
/// };
///
/// union GETATTR4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         GETATTR4resok  resok4;
///     default:
///         void;
/// };
///
/// struct GETFH4resok {
///     nfs_fh4        object;
/// };
///
/// union GETFH4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         GETFH4resok    resok4;
///     default:
///         void;
/// };
///
/// struct LINK4args {
///     /* SAVED_FH: source object */
///     /* CURRENT_FH: target directory */
///     component4     newname;

```

```

/// };
///
/// struct LINK4resok {
///     change_info4    cinfo;
/// };
///
/// union LINK4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         LINK4resok resok4;
///     default:
///         void;
/// };
///
/// /*
///  * For LOCK, transition from open_stateid and lock_owner
///  * to a lock stateid.
///  */
/// struct open_to_lock_owner4 {
///     seqid4          open_seqid;
///     stateid4        open_stateid;
///     seqid4          lock_seqid;
///     lock_owner4     lock_owner;
/// };
///
/// /*
///  * For LOCK, existing lock stateid continues to request new
///  * file lock for the same lock_owner and open_stateid.
///  */
/// struct exist_lock_owner4 {
///     stateid4        lock_stateid;
///     seqid4          lock_seqid;
/// };
///
/// union locker4 switch (bool new_lock_owner) {
///     case TRUE:
///         open_to_lock_owner4    open_owner;
///     case FALSE:
///         exist_lock_owner4      lock_owner;
/// };
///
/// /*
///  * LOCK/LOCKT/LOCKU: Record lock management
///  */
/// struct LOCK4args {
///     /* CURRENT_FH: file */
///     nfs_lock_type4 locktype;
///     bool            reclaim;
///     offset4        offset;

```

```

    ///         length4         length;
    ///         locker4         locker;
    /// };
    ///
    /// struct LOCK4denied {
    ///         offset4         offset;
    ///         length4         length;
    ///         nfs_lock_type4  locktype;
    ///         lock_owner4     owner;
    /// };
    ///
    /// struct LOCK4resok {
    ///         stateid4         lock_stateid;
    /// };
    ///
    /// union LOCK4res switch (nfsstat4 status) {
    ///     case NFS4_OK:
    ///         LOCK4resok         resok4;
    ///     case NFS4ERR_DENIED:
    ///         LOCK4denied        denied;
    ///     default:
    ///         void;
    /// };
    ///
    /// struct LOCKT4args {
    ///         /* CURRENT_FH: file */
    ///         nfs_lock_type4  locktype;
    ///         offset4         offset;
    ///         length4         length;
    ///         lock_owner4     owner;
    /// };
    ///
    /// union LOCKT4res switch (nfsstat4 status) {
    ///     case NFS4ERR_DENIED:
    ///         LOCK4denied        denied;
    ///     case NFS4_OK:
    ///         void;
    ///     default:
    ///         void;
    /// };
    ///
    /// struct LOCKU4args {
    ///         /* CURRENT_FH: file */
    ///         nfs_lock_type4  locktype;
    ///         seqid4          seqid;
    ///         stateid4        lock_stateid;
    ///         offset4         offset;
    ///         length4         length;

```

```

/// };
///
/// union LOCKU4res switch (nfsstat4 status) {
///   case  NFS4_OK:
///       stateid4      lock_stateid;
///   default:
///       void;
/// };
///
/// struct LOOKUP4args {
///     /* CURRENT_FH: directory */
///     component4     objname;
/// };
///
/// struct LOOKUP4res {
///     /* New CURRENT_FH: object */
///     nfsstat4      status;
/// };
///
/// struct LOOKUP4res {
///     /* new CURRENT_FH: parent directory */
///     nfsstat4      status;
/// };
///
/// struct NVERIFY4args {
///     /* CURRENT_FH: object */
///     fattr4        obj_attributes;
/// };
///
/// struct NVERIFY4res {
///     nfsstat4      status;
/// };
///
/// /*
///  * Various definitions for OPEN
///  */
/// enum createmode4 {
///     UNCHECKED4      = 0,
///     GUARDED4        = 1,
///     /* Deprecated in NFSv4.1. */
///     EXCLUSIVE4      = 2,
///     /*
///      * New to NFSv4.1. If session is persistent,
///      * GUARDED4 MUST be used. Otherwise, use
///      * EXCLUSIVE4_1 instead of EXCLUSIVE4.
///      */
///     EXCLUSIVE4_1    = 3
/// };

```

```

///
/// struct creatverfattn {
///     verifier4      cva_verf;
///     fattn4         cva_attr;
/// };
///
/// union createhow4 switch (createmode4 mode) {
///     case UNCHECKED4:
///     case GUARDED4:
///         fattn4         createattr;
///     case EXCLUSIVE4:
///         verifier4      createverf;
///     case EXCLUSIVE4_1:
///         creatverfattn ch_createboth;
/// };
///
/// enum opentype4 {
///     OPEN4_NOCREATE    = 0,
///     OPEN4_CREATE      = 1
/// };
///
/// union openflag4 switch (opentype4 opentype) {
///     case OPEN4_CREATE:
///         createhow4     how;
///     default:
///         void;
/// };
///
/// /* Next definitions used for OPEN delegation */
/// enum limit_by4 {
///     NFS_LIMIT_SIZE      = 1,
///     NFS_LIMIT_BLOCKS    = 2
///     /* others as needed */
/// };
///
/// struct nfs_modified_limit4 {
///     uint32_t            num_blocks;
///     uint32_t            bytes_per_block;
/// };
///
/// union nfs_space_limit4 switch (limit_by4 limitby) {
///     /* limit specified as file size */
///     case NFS_LIMIT_SIZE:
///         uint64_t         filesize;
///     /* limit specified by number of blocks */
///     case NFS_LIMIT_BLOCKS:
///         nfs_modified_limit4 mod_blocks;
/// };

```

```

///
/// /*
///  * Share Access and Deny constants for open argument
///  */
/// const OPEN4_SHARE_ACCESS_READ    = 0x00000001;
/// const OPEN4_SHARE_ACCESS_WRITE    = 0x00000002;
/// const OPEN4_SHARE_ACCESS_BOTH     = 0x00000003;
///
/// const OPEN4_SHARE_DENY_NONE       = 0x00000000;
/// const OPEN4_SHARE_DENY_READ       = 0x00000001;
/// const OPEN4_SHARE_DENY_WRITE      = 0x00000002;
/// const OPEN4_SHARE_DENY_BOTH       = 0x00000003;
///
///
/// /* new flags for share_access field of OPEN4args */
/// const OPEN4_SHARE_ACCESS_WANT_DELEG_MASK      = 0xFF00;
/// const OPEN4_SHARE_ACCESS_WANT_NO_PREFERENCE  = 0x0000;
/// const OPEN4_SHARE_ACCESS_WANT_READ_DELEG     = 0x0100;
/// const OPEN4_SHARE_ACCESS_WANT_WRITE_DELEG    = 0x0200;
/// const OPEN4_SHARE_ACCESS_WANT_ANY_DELEG      = 0x0300;
/// const OPEN4_SHARE_ACCESS_WANT_NO_DELEG      = 0x0400;
/// const OPEN4_SHARE_ACCESS_WANT_CANCEL        = 0x0500;
///
/// const
/// OPEN4_SHARE_ACCESS_WANT_SIGNAL_DELEG_WHEN_RESRC_AVAIL
/// = 0x10000;
///
/// const
/// OPEN4_SHARE_ACCESS_WANT_PUSH_DELEG_WHEN_UNCONTENDED
/// = 0x20000;
///
/// enum open_delegation_type4 {
///     OPEN_DELEGATE_NONE        = 0,
///     OPEN_DELEGATE_READ        = 1,
///     OPEN_DELEGATE_WRITE       = 2,
///     OPEN_DELEGATE_NONE_EXT    = 3 /* new to v4.1 */
/// };
///
/// enum open_claim_type4 {
///     /*
///      * Not a reclaim.
///      */
///     CLAIM_NULL                = 0,
///
///     CLAIM_PREVIOUS            = 1,
///     CLAIM_DELEGATE_CUR        = 2,
///     CLAIM_DELEGATE_PREV       = 3,
///
///

```

```

///      /*
///      * Not a reclaim.
///      *
///      * Like CLAIM_NULL, but object identified
///      * by the current filehandle.
///      */
///      CLAIM_FH                = 4, /* new to v4.1 */
///
///      /*
///      * Like CLAIM_DELEGATE_CUR, but object identified
///      * by current filehandle.
///      */
///      CLAIM_DELEG_CUR_FH      = 5, /* new to v4.1 */
///
///      /*
///      * Like CLAIM_DELEGATE_PREV, but object identified
///      * by current filehandle.
///      */
///      CLAIM_DELEG_PREV_FH     = 6 /* new to v4.1 */
/// };
///
/// struct open_claim_delegate_cur4 {
///     stateid4      delegate_stateid;
///     component4    file;
/// };
///
/// union open_claim4 switch (open_claim_type4 claim) {
///     /*
///     * No special rights to file.
///     * Ordinary OPEN of the specified file.
///     */
///     case CLAIM_NULL:
///         /* CURRENT_FH: directory */
///         component4    file;
///     /*
///     * Right to the file established by an
///     * open previous to server reboot. File
///     * identified by filehandle obtained at
///     * that time rather than by name.
///     */
///     case CLAIM_PREVIOUS:
///         /* CURRENT_FH: file being reclaimed */
///         open_delegation_type4    delegate_type;
///     /*
///     * Right to file based on a delegation
///     * granted by the server. File is
///     * specified by name.

```

```

/// */
/// case CLAIM_DELEGATE_CUR:
///     /* CURRENT_FH: directory */
///     open_claim_delegate_cur4         delegate_cur_info;
///
/// /*
///  * Right to file based on a delegation
///  * granted to a previous boot instance
///  * of the client.  File is specified by name.
///  */
/// case CLAIM_DELEGATE_PREV:
///     /* CURRENT_FH: directory */
///     component4         file_delegate_prev;
///
/// /*
///  * Like CLAIM_NULL.  No special rights
///  * to file.  Ordinary OPEN of the
///  * specified file by current filehandle.
///  */
/// case CLAIM_FH: /* new to v4.1 */
///     /* CURRENT_FH: regular file to open */
///     void;
///
/// /*
///  * Like CLAIM_DELEGATE_PREV.  Right to file based on a
///  * delegation granted to a previous boot
///  * instance of the client.  File is identified by
///  * by filehandle.
///  */
/// case CLAIM_DELEG_PREV_FH: /* new to v4.1 */
///     /* CURRENT_FH: file being opened */
///     void;
///
/// /*
///  * Like CLAIM_DELEGATE_CUR.  Right to file based on
///  * a delegation granted by the server.
///  * File is identified by filehandle.
///  */
/// case CLAIM_DELEG_CUR_FH: /* new to v4.1 */
///     /* CURRENT_FH: file being opened */
///     stateid4         oc_delegate_stateid;
///
/// };
///
/// /*
///  * OPEN: Open a file, potentially receiving an open delegation
///  */
/// struct OPEN4args {

```

```

///      seqid4          seqid;
///      uint32_t        share_access;
///      uint32_t        share_deny;
///      open_owner4     owner;
///      openflag4       openhow;
///      open_claim4     claim;
/// };
///
/// struct open_read_delegation4 {
///   stateid4 stateid; /* Stateid for delegation*/
///   bool      recall; /* Pre-recalled flag for
///                     delegations obtained
///                     by reclaim (CLAIM_PREVIOUS) */
///
///   nfsace4 permissions; /* Defines users who don't
///                         need an ACCESS call to
///                         open for read */
/// };
///
/// struct open_write_delegation4 {
///   stateid4 stateid; /* Stateid for delegation */
///   bool      recall; /* Pre-recalled flag for
///                     delegations obtained
///                     by reclaim
///                     (CLAIM_PREVIOUS) */
///
///   nfs_space_limit4
///     space_limit; /* Defines condition that
///                 the client must check to
///                 determine whether the
///                 file needs to be flushed
///                 to the server on close. */
///
///   nfsace4 permissions; /* Defines users who don't
///                         need an ACCESS call as
///                         part of a delegated
///                         open. */
/// };
///
/// enum why_no_delegation4 { /* new to v4.1 */
///   WND4_NOT_WANTED          = 0,
///   WND4_CONTENTION         = 1,
///   WND4_RESOURCE           = 2,
///   WND4_NOT_SUPP_FTYPE     = 3,
///   WND4_WRITE_DELEG_NOT_SUPP_FTYPE = 4,
///   WND4_NOT_SUPP_UPGRADE   = 5,
///   WND4_NOT_SUPP_DOWNGRADE = 6,

```

```

    ///          WND4_CANCELLED          = 7,
    ///          WND4_IS_DIR             = 8
    /// };
    ///
    /// union open_none_delegation4 /* new to v4.1 */
    /// switch (why_no_delegation4 ond_why) {
    ///     case WND4_CONTENTION:
    ///         bool ond_server_will_push_deleg;
    ///     case WND4_RESOURCE:
    ///         bool ond_server_will_signal_avail;
    ///     default:
    ///         void;
    /// };
    ///
    /// union open_delegation4
    /// switch (open_delegation_type4 delegation_type) {
    ///     case OPEN_DELEGATE_NONE:
    ///         void;
    ///     case OPEN_DELEGATE_READ:
    ///         open_read_delegation4 read;
    ///     case OPEN_DELEGATE_WRITE:
    ///         open_write_delegation4 write;
    ///     case OPEN_DELEGATE_NONE_EXT: /* new to v4.1 */
    ///         open_none_delegation4 od_whynone;
    /// };
    ///
    /// /*
    ///  * Result flags
    ///  */
    ///
    /// /* Client must confirm open */
    /// const OPEN4_RESULT_CONFIRM          = 0x00000002;
    /// /* Type of file locking behavior at the server */
    /// const OPEN4_RESULT_LOCKTYPE_POSIX = 0x00000004;
    /// /* Server will preserve file if removed while open */
    /// const OPEN4_RESULT_PRESERVE_UNLINKED = 0x00000008;
    ///
    /// /*
    ///  * Server may use CB_NOTIFY_LOCK on locks
    ///  * derived from this open
    ///  */
    /// const OPEN4_RESULT_MAY_NOTIFY_LOCK = 0x00000020;
    ///
    /// struct OPEN4resok {
    ///     stateid4      stateid;      /* Stateid for open */
    ///     change_info4  cinfo;        /* Directory Change Info */
    ///     uint32_t      rflags;       /* Result flags */
    ///     bitmap4       attrset;      /* attribute set for create*/

```

```

/// open_delegation4 delegation; /* Info on any open
///                               delegation */
/// };
///
/// union OPEN4res switch (nfsstat4 status) {
///   case NFS4_OK:
///     /* New CURRENT_FH: opened file */
///     OPEN4resok      resok4;
///   default:
///     void;
/// };
///
/// struct OPENATTR4args {
///   /* CURRENT_FH: object */
///   bool   createdir;
/// };
///
/// struct OPENATTR4res {
///   /*
///    * If status is NFS4_OK,
///    * new CURRENT_FH: named attribute
///    * directory
///    */
///   nfsstat4      status;
/// };
///
/// /* obsolete in NFSv4.1 */
/// struct OPEN_CONFIRM4args {
///   /* CURRENT_FH: opened file */
///   stateid4      open_stateid;
///   seqid4        seqid;
/// };
///
/// struct OPEN_CONFIRM4resok {
///   stateid4      open_stateid;
/// };
///
/// union OPEN_CONFIRM4res switch (nfsstat4 status) {
///   case NFS4_OK:
///     OPEN_CONFIRM4resok      resok4;
///   default:
///     void;
/// };
///
/// struct OPEN_DOWNGRADE4args {
///   /* CURRENT_FH: opened file */
///   stateid4      open_stateid;
///   seqid4        seqid;

```

```

    ///      uint32_t      share_access;
    ///      uint32_t      share_deny;
    /// };
    ///
    /// struct OPEN_DOWNGRADE4resok {
    ///      stateid4      open_stateid;
    /// };
    ///
    /// union OPEN_DOWNGRADE4res switch(nfsstat4 status) {
    ///      case NFS4_OK:
    ///          OPEN_DOWNGRADE4resok      resok4;
    ///      default:
    ///          void;
    /// };
    ///
    /// struct PUTFH4args {
    ///      nfs_fh4      object;
    /// };
    ///
    /// struct PUTFH4res {
    ///      /*
    ///       * If status is NFS4_OK,
    ///       *   new CURRENT_FH: argument to PUTFH
    ///       */
    ///      nfsstat4      status;
    /// };
    ///
    /// struct PUTPUBFH4res {
    ///      /*
    ///       * If status is NFS4_OK,
    ///       *   new CURRENT_FH: public fh
    ///       */
    ///      nfsstat4      status;
    /// };
    ///
    /// struct PUTROOTFH4res {
    ///      /*
    ///       * If status is NFS4_OK,
    ///       *   new CURRENT_FH: root fh
    ///       */
    ///      nfsstat4      status;
    /// };
    ///
    /// struct READ4args {
    ///      /* CURRENT_FH: file */
    ///      stateid4      stateid;
    ///      offset4      offset;
    ///      count4      count;

```

```

/// };
///
/// struct READ4resok {
///     bool          eof;
///     opaque        data<>;
/// };
///
/// union READ4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         READ4resok    resok4;
///     default:
///         void;
/// };
///
/// struct REaddir4args {
///     /* CURRENT_FH: directory */
///     nfs_cookie4     cookie;
///     verifier4       cookieverf;
///     count4          dircount;
///     count4          maxcount;
///     bitmap4         attr_request;
/// };
///
/// struct entry4 {
///     nfs_cookie4     cookie;
///     component4      name;
///     fattr4          attrs;
///     entry4          *nextentry;
/// };
///
/// struct dirlist4 {
///     entry4          *entries;
///     bool            eof;
/// };
///
/// struct REaddir4resok {
///     verifier4       cookieverf;
///     dirlist4        reply;
/// };
///
/// union REaddir4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         REaddir4resok    resok4;
///     default:
///         void;
/// };
///

```

```
///
/// struct READLINK4resok {
///     linktext4      link;
/// };
///
/// union READLINK4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         READLINK4resok resok4;
///     default:
///         void;
/// };
///
/// struct REMOVE4args {
///     /* CURRENT_FH: directory */
///     component4      target;
/// };
///
/// struct REMOVE4resok {
///     change_info4    cinfo;
/// };
///
/// union REMOVE4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         REMOVE4resok  resok4;
///     default:
///         void;
/// };
///
/// struct RENAME4args {
///     /* SAVED_FH: source directory */
///     component4      oldname;
///     /* CURRENT_FH: target directory */
///     component4      newname;
/// };
///
/// struct RENAME4resok {
///     change_info4    source_cinfo;
///     change_info4    target_cinfo;
/// };
///
/// union RENAME4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         RENAME4resok  resok4;
///     default:
///         void;
/// };
///
/// /* Obsolete in NFSv4.1 */
```

```

/// struct RENEW4args {
///     clientid4      clientid;
/// };
///
/// struct RENEW4res {
///     nfsstat4       status;
/// };
///
/// struct RESTOREFH4res {
///     /*
///      * If status is NFS4_OK,
///      *   new CURRENT_FH: value of saved fh
///      */
///     nfsstat4       status;
/// };
///
/// struct SAVEFH4res {
///     /*
///      * If status is NFS4_OK,
///      *   new SAVED_FH: value of current fh
///      */
///     nfsstat4       status;
/// };
///
/// struct SECINFO4args {
///     /* CURRENT_FH: directory */
///     component4     name;
/// };
///
/// /*
///  * From RFC 2203
///  */
/// enum rpc_gss_svc_t {
///     RPC_GSS_SVC_NONE           = 1,
///     RPC_GSS_SVC_INTEGRITY      = 2,
///     RPC_GSS_SVC_PRIVACY        = 3
/// };
///
/// struct rpcsec_gss_info {
///     sec_oid4      oid;
///     qop4          qop;
///     rpc_gss_svc_t service;
/// };
///
/// /* RPCSEC_GSS has a value of '6' - See RFC 2203 */
/// union secinfo4 switch (uint32_t flavor) {
///     case RPCSEC_GSS:
///         rpcsec_gss_info      flavor_info;

```

```

/// default:
///     void;
/// };
///
/// typedef secinfo4 SECINFO4resok<>;
///
/// union SECINFO4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         /* CURRENTFH: consumed */
///         SECINFO4resok resok4;
///     default:
///         void;
/// };
///
/// struct SETATTR4args {
///     /* CURRENT_FH: target object */
///     stateid4      stateid;
///     fattr4        obj_attributes;
/// };
///
/// struct SETATTR4res {
///     nfsstat4      status;
///     bitmap4       attrset;
/// };
///
/// /* Obsolete in NFSv4.1 */
/// struct SETCLIENTID4args {
///     nfs_client_id4 client;
///     cb_client4     callback;
///     uint32_t       callback_ident;
/// };
///
/// struct SETCLIENTID4resok {
///     clientid4      clientid;
///     verifier4     setclientid_confirm;
/// };
///
/// union SETCLIENTID4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         SETCLIENTID4resok      resok4;
///     case NFS4ERR_CLID_INUSE:
///         clientaddr4      client_using;
///     default:
///         void;
/// };
///
/// /* Obsolete in NFSv4.1 */
/// struct SETCLIENTID_CONFIRM4args {

```

```

    ///      clientid4      clientid;
    ///      verifier4      setclientid_confirm;
    /// };
    ///
    /// struct SETCLIENTID_CONFIRM4res {
    ///      nfsstat4      status;
    /// };
    ///
    /// struct VERIFY4args {
    ///      /* CURRENT_FH: object */
    ///      fattr4      obj_attributes;
    /// };
    ///
    /// struct VERIFY4res {
    ///      nfsstat4      status;
    /// };
    ///
    /// enum stable_how4 {
    ///      UNSTABLE4      = 0,
    ///      DATA_SYNC4      = 1,
    ///      FILE_SYNC4      = 2
    /// };
    ///
    /// struct WRITE4args {
    ///      /* CURRENT_FH: file */
    ///      stateid4      stateid;
    ///      offset4      offset;
    ///      stable_how4      stable;
    ///      opaque      data<>;
    /// };
    ///
    /// struct WRITE4resok {
    ///      count4      count;
    ///      stable_how4      committed;
    ///      verifier4      writeverf;
    /// };
    ///
    /// union WRITE4res switch (nfsstat4 status) {
    ///      case NFS4_OK:
    ///          WRITE4resok      resok4;
    ///      default:
    ///          void;
    /// };
    ///
    /// /* Obsolete in NFSv4.1 */
    /// struct RELEASE_LOCKOWNER4args {
    ///      lock_owner4      lock_owner;
    /// };

```

```

///
/// struct RELEASE_LOCKOWNER4res {
///     nfsstat4      status;
/// };
///
/// struct ILLEGAL4res {
///     nfsstat4      status;
/// };
///
/// typedef opaque gsshandle4_t<>;
///
/// struct gss_cb_handles4 {
///     rpc_gss_svc_t      gcbp_service; /* RFC 2203 */
///     gsshandle4_t      gcbp_handle_from_server;
///     gsshandle4_t      gcbp_handle_from_client;
/// };
///
/// union callback_sec_parms4 switch (uint32_t cb_secflavor) {
/// case AUTH_NONE:
///     void;
/// case AUTH_SYS:
///     authsys_parms      cbsp_sys_cred; /* RFC 1831 */
/// case RPCSEC_GSS:
///     gss_cb_handles4   cbsp_gss_handles;
/// };
///
/// struct BACKCHANNEL_CTL4args {
///     uint32_t          bca_cb_program;
///     callback_sec_parms4  bca_sec_parms<>;
/// };
///
/// struct BACKCHANNEL_CTL4res {
///     nfsstat4          bcr_status;
/// };
///
/// enum channel_dir_from_client4 {
///     CDFC4_FORE          = 0x1,
///     CDFC4_BACK          = 0x2,
///     CDFC4_FORE_OR_BOTH = 0x3,
///     CDFC4_BACK_OR_BOTH = 0x7
/// };
///
/// struct BIND_CONN_TO_SESSION4args {
///     sessionid4      bctsa_sessid;
///
///     channel_dir_from_client4
///     bctsa_dir;
/// }

```

```

/// bool                bctsa_use_conn_in_rdma_mode;
/// };
///
/// enum channel_dir_from_server4 {
///     CDFS4_FORE        = 0x1,
///     CDFS4_BACK        = 0x2,
///     CDFS4_BOTH        = 0x3
/// };
///
/// struct BIND_CONN_TO_SESSION4resok {
///     sessionid4        bctsr_sessid;
///
///     channel_dir_from_server4
///         bctsr_dir;
///
///     bool                bctsr_use_conn_in_rdma_mode;
/// };
///
/// union BIND_CONN_TO_SESSION4res
///     switch (nfsstat4 bctsr_status) {
///
///     case NFS4_OK:
///         BIND_CONN_TO_SESSION4resok
///             bctsr_resok4;
///
///     default:
///         void;
///     };
///
/// const EXCHGID4_FLAG_SUPP_MOVED_REFERER    = 0x00000001;
/// const EXCHGID4_FLAG_SUPP_MOVED_MIGR      = 0x00000002;
///
/// const EXCHGID4_FLAG_BIND_PRINC_STATEID    = 0x00000100;
///
/// const EXCHGID4_FLAG_USE_NON_PNFS          = 0x00010000;
/// const EXCHGID4_FLAG_USE_PNFS_MDS          = 0x00020000;
/// const EXCHGID4_FLAG_USE_PNFS_DS           = 0x00040000;
///
/// const EXCHGID4_FLAG_MASK_PNFS             = 0x00070000;
///
/// const EXCHGID4_FLAG_UPD_CONFIRMED_REC_A    = 0x40000000;
/// const EXCHGID4_FLAG_CONFIRMED_R           = 0x80000000;
///
/// struct state_protect_ops4 {
///     bitmap4 spo_must_enforce;
///     bitmap4 spo_must_allow;
/// };
///
/// struct ssv_sp_parms4 {

```

```

    ///         state_protect_ops4         ssp_ops;
    ///         sec_oid4                   ssp_hash_algs<>;
    ///         sec_oid4                   ssp_encr_algs<>;
    ///         uint32_t                    ssp_window;
    ///         uint32_t                    ssp_num_gss_handles;
    /// };
    ///
    /// enum state_protect_how4 {
    ///     SP4_NONE = 0,
    ///     SP4_MACH_CRED = 1,
    ///     SP4_SSV = 2
    /// };
    ///
    /// union state_protect4_a switch(state_protect_how4 spa_how) {
    ///     case SP4_NONE:
    ///         void;
    ///     case SP4_MACH_CRED:
    ///         state_protect_ops4         spa_mach_ops;
    ///     case SP4_SSV:
    ///         ssv_sp_parms4              spa_ssv_parms;
    /// };
    ///
    /// struct EXCHANGE_ID4args {
    ///     client_owner4                 eia_clientowner;
    ///     uint32_t                      eia_flags;
    ///     state_protect4_a              eia_state_protect;
    ///     nfs_impl_id4                  eia_client_impl_id<1>;
    /// };
    ///
    /// struct ssv_prot_info4 {
    ///     state_protect_ops4            spi_ops;
    ///     uint32_t                      spi_hash_alg;
    ///     uint32_t                      spi_encr_alg;
    ///     uint32_t                      spi_ssv_len;
    ///     uint32_t                      spi_window;
    ///     gsshandle4_t                  spi_handles<>;
    /// };
    ///
    /// union state_protect4_r switch(state_protect_how4 spr_how) {
    ///     case SP4_NONE:
    ///         void;
    ///     case SP4_MACH_CRED:
    ///         state_protect_ops4            spr_mach_ops;
    ///     case SP4_SSV:
    ///         ssv_prot_info4              spr_ssv_info;
    /// };
    ///
    /// struct EXCHANGE_ID4resok {

```

```

/// clientid4      eir_clientid;
/// sequenceid4   eir_sequenceid;
/// uint32_t      eir_flags;
/// state_protect4_r eir_state_protect;
/// server_owner4  eir_server_owner;
/// opaque        eir_server_scope<NFS4_OPAQUE_LIMIT>;
/// nfs_impl_id4  eir_server_impl_id<1>;
/// };
///
/// union EXCHANGE_ID4res switch (nfsstat4 eir_status) {
/// case NFS4_OK:
///   EXCHANGE_ID4resok      eir_resok4;
///
/// default:
///   void;
/// };
///
/// struct channel_attrs4 {
///     count4      ca_headerpadsize;
///     count4      ca_maxrequestsize;
///     count4      ca_maxresponsesize;
///     count4      ca_maxresponsesize_cached;
///     count4      ca_maxoperations;
///     count4      ca_maxrequests;
///     uint32_t    ca_rdma_ird<1>;
/// };
///
/// const CREATE_SESSION4_FLAG_PERSIST      = 0x00000001;
/// const CREATE_SESSION4_FLAG_CONN_BACK_CHAN = 0x00000002;
/// const CREATE_SESSION4_FLAG_CONN_RDMA    = 0x00000004;
///
/// struct CREATE_SESSION4args {
///     clientid4      csa_clientid;
///     sequenceid4    csa_sequence;
///
///     uint32_t      csa_flags;
///
///     channel_attrs4 csa_fore_chan_attrs;
///     channel_attrs4 csa_back_chan_attrs;
///
///     uint32_t      csa_cb_program;
///     callback_sec_parms4 csa_sec_parms<>;
/// };
///
/// struct CREATE_SESSION4resok {
///     sessionid4    csr_sessionid;
///     sequenceid4   csr_sequence;
///

```

```

///      uint32_t          csr_flags;
///
///      channel_attr4     csr_fore_chan_attr;
///      channel_attr4     csr_back_chan_attr;
/// };
///
/// union CREATE_SESSION4res switch (nfsstat4 csr_status) {
/// case NFS4_OK:
///      CREATE_SESSION4resok  csr_resok4;
/// default:
///      void;
/// };
///
/// struct DESTROY_SESSION4args {
///      sessionid4          dsa_sessionid;
/// };
///
/// struct DESTROY_SESSION4res {
///      nfsstat4            dsr_status;
/// };
///
/// struct FREE_STATEID4args {
///      stateid4            fsa_stateid;
/// };
///
/// struct FREE_STATEID4res {
///      nfsstat4            fsr_status;
/// };
///
/// typedef nfstime4 attr_notice4;
///
/// struct GET_DIR_DELEGATION4args {
///      /* CURRENT_FH: delegated directory */
///      bool                gdda_signal_deleg_avail;
///      bitmap4             gdda_notification_types;
///      attr_notice4        gdda_child_attr_delay;
///      attr_notice4        gdda_dir_attr_delay;
///      bitmap4             gdda_child_attributes;
///      bitmap4             gdda_dir_attributes;
/// };
/// struct GET_DIR_DELEGATION4resok {
///      verifier4           gddr_cookieverf;
///      /* Stateid for get_dir_delegation */
///      stateid4            gddr_stateid;
///      /* Which notifications can the server support */
///      bitmap4             gddr_notification;
///      bitmap4             gddr_child_attributes;

```

```

    ///         bitmap4           gddr_dir_attributes;
    /// };
    ///
    /// enum gddrnf4_status {
    ///     GDD4_OK           = 0,
    ///     GDD4_UNAVAIL     = 1
    /// };
    ///
    /// union GET_DIR_DELEGATION4res_non_fatal
    ///     switch (gddrnf4_status gddrnf_status) {
    ///     case GDD4_OK:
    ///         GET_DIR_DELEGATION4resok           gddrnf_resok4;
    ///     case GDD4_UNAVAIL:
    ///         bool                               gddrnf_will_signal_deleg_avail;
    ///     };
    ///
    /// union GET_DIR_DELEGATION4res
    ///     switch (nfsstat4 gddr_status) {
    ///     case NFS4_OK:
    ///         GET_DIR_DELEGATION4res_non_fatal     gddr_res_non_fatal4;
    ///     default:
    ///         void;
    ///     };
    ///
    /// struct GETDEVICEINFO4args {
    ///     deviceid4           gdia_device_id;
    ///     layouttype4        gdia_layout_type;
    ///     count4              gdia_maxcount;
    ///     bitmap4            gdia_notify_types;
    /// };
    ///
    /// struct GETDEVICEINFO4resok {
    ///     device_addr4        gdir_device_addr;
    ///     bitmap4            gdir_notification;
    /// };
    ///
    /// union GETDEVICEINFO4res switch (nfsstat4 gdir_status) {
    ///     case NFS4_OK:
    ///         GETDEVICEINFO4resok           gdir_resok4;
    ///     case NFS4ERR_TOOSMALL:
    ///         count4                       gdir_mincount;
    ///     default:
    ///         void;
    ///     };
    ///
    /// struct GETDEVICELIST4args {
    ///     /* CURRENT_FH: object belonging to the file system */
    ///     layouttype4        gdla_layout_type;

```

```

///
///      /* number of deviceIDs to return */
///      count4          gdla_maxdevices;
///
///      nfs_cookie4     gdla_cookie;
///      verifier4       gdla_cookieverf;
/// };
///
/// struct GETDEVICELIST4resok {
///      nfs_cookie4          gdlr_cookie;
///      verifier4           gdlr_cookieverf;
///      deviceid4           gdlr_deviceid_list<>;
///      bool                gdlr_eof;
/// };
///
/// union GETDEVICELIST4res switch (nfsstat4 gdlr_status) {
/// case NFS4_OK:
///      GETDEVICELIST4resok      gdlr_resok4;
/// default:
///      void;
/// };
///
/// union newtime4 switch (bool nt_timechanged) {
/// case TRUE:
///      nfstime4                nt_time;
/// case FALSE:
///      void;
/// };
///
/// union newoffset4 switch (bool no_newoffset) {
/// case TRUE:
///      offset4                 no_offset;
/// case FALSE:
///      void;
/// };
///
/// struct LAYOUTCOMMIT4args {
///      /* CURRENT_FH: file */
///      offset4                 loca_offset;
///      length4                 loca_length;
///      bool                    loca_reclaim;
///      stateid4                loca_stateid;
///      newoffset4              loca_last_write_offset;
///      newtime4                loca_time_modify;
///      layoutupdate4           loca_layoutupdate;
/// };
///
/// union newsize4 switch (bool ns_sizechanged) {
/// case TRUE:

```

```

    length4          ns_size;
    case FALSE:
    void;
};
//
// struct LAYOUTCOMMIT4resok {
//     newsize4          locr_newsize;
// };
//
// union LAYOUTCOMMIT4res switch (nfsstat4 locr_status) {
// case NFS4_OK:
//     LAYOUTCOMMIT4resok          locr_resok4;
// default:
//     void;
// };
//
// struct LAYOUTGET4args {
//     /* CURRENT_FH: file */
//     bool          loga_signal_layout_avail;
//     layouttype4          loga_layout_type;
//     layoutiomode4          loga_iomode;
//     offset4          loga_offset;
//     length4          loga_length;
//     length4          loga_minlength;
//     stateid4          loga_stateid;
//     count4          loga_maxcount;
// };
// struct LAYOUTGET4resok {
//     bool          logr_return_on_close;
//     stateid4          logr_stateid;
//     layout4          logr_layout<>;
// };
//
// union LAYOUTGET4res switch (nfsstat4 logr_status) {
// case NFS4_OK:
//     LAYOUTGET4resok          logr_resok4;
// case NFS4ERR_LAYOUTTRYLATER:
//     bool          logr_will_signal_layout_avail;
// default:
//     void;
// };
//
// struct LAYOUTRETURN4args {
//     /* CURRENT_FH: file */
//     bool          lora_reclaim;
//     layouttype4          lora_layout_type;
//     layoutiomode4          lora_iomode;

```

```

///          layoutreturn4          lora_layoutreturn;
/// };
///
/// union layoutreturn_stateid switch (bool lrs_present) {
/// case TRUE:
///     stateid4          lrs_stateid;
/// case FALSE:
///     void;
/// };
///
/// union LAYOUTRETURN4res switch (nfsstat4 lorr_status) {
/// case NFS4_OK:
///     layoutreturn_stateid    lorr_stateid;
/// default:
///     void;
/// };
///
/// enum secinfo_style4 {
///     SECINFO_STYLE4_CURRENT_FH          = 0,
///     SECINFO_STYLE4_PARENT              = 1
/// };
///
/// /* CURRENT_FH: object or child directory */
/// typedef secinfo_style4 SECINFO_NO_NAME4args;
///
/// /* CURRENTFH: consumed if status is NFS4_OK */
/// typedef SECINFO4res SECINFO_NO_NAME4res;
///
/// struct SEQUENCE4args {
///     sessionid4    sa_sessionid;
///     sequenceid4   sa_sequenceid;
///     slotid4       sa_slotid;
///     slotid4       sa_highest_slotid;
///     bool          sa_cachethis;
/// };
///
/// const SEQ4_STATUS_CB_PATH_DOWN          = 0x00000001;
/// const SEQ4_STATUS_CB_GSS_CONTEXTS_EXPIRING = 0x00000002;
/// const SEQ4_STATUS_CB_GSS_CONTEXTS_EXPIRED = 0x00000004;
/// const SEQ4_STATUS_EXPIRED_ALL_STATE_REVOKED = 0x00000008;
/// const SEQ4_STATUS_EXPIRED_SOME_STATE_REVOKED = 0x00000010;
/// const SEQ4_STATUS_ADMIN_STATE_REVOKED = 0x00000020;
/// const SEQ4_STATUS_RECALLABLE_STATE_REVOKED = 0x00000040;
/// const SEQ4_STATUS_LEASE_MOVED = 0x00000080;
/// const SEQ4_STATUS_RESTART_RECLAIM_NEEDED = 0x00000100;
/// const SEQ4_STATUS_CB_PATH_DOWN_SESSION = 0x00000200;
/// const SEQ4_STATUS_BACKCHANNEL_FAULT = 0x00000400;

```

```

/// const SEQ4_STATUS_DEVID_CHANGED          = 0x00000800;
/// const SEQ4_STATUS_DEVID_DELETED         = 0x00001000;
///
/// struct SEQUENCE4resok {
///     sessionid4      sr_sessionid;
///     sequenceid4     sr_sequenceid;
///     slotid4         sr_slotid;
///     slotid4         sr_highest_slotid;
///     slotid4         sr_target_highest_slotid;
///     uint32_t        sr_status_flags;
/// };
///
/// union SEQUENCE4res switch (nfsstat4 sr_status) {
/// case NFS4_OK:
///     SEQUENCE4resok  sr_resok4;
/// default:
///     void;
/// };
///
/// struct ssa_digest_input4 {
///     SEQUENCE4args  sdi_seqargs;
/// };
///
/// struct SET_SSV4args {
///     opaque         ssa_ssv<>;
///     opaque         ssa_digest<>;
/// };
///
/// struct ssr_digest_input4 {
///     SEQUENCE4res  sdi_seqres;
/// };
///
/// struct SET_SSV4resok {
///     opaque         ssr_digest<>;
/// };
///
/// union SET_SSV4res switch (nfsstat4 ssr_status) {
/// case NFS4_OK:
///     SET_SSV4resok  ssr_resok4;
/// default:
///     void;
/// };
///
/// struct TEST_STATEID4args {
///     stateid4       ts_stateids<>;
/// };
///
/// struct TEST_STATEID4resok {

```

```

    ///          nfsstat4          tsr_status_codes<>;
    /// };
    ///
    /// union TEST_STATEID4res switch (nfsstat4 tsr_status) {
    ///     case NFS4_OK:
    ///         TEST_STATEID4resok tsr_resok4;
    ///     default:
    ///         void;
    /// };
    ///
    /// union deleg_claim4 switch (open_claim_type4 dc_claim) {
    ///     /*
    ///     * No special rights to object. Ordinary delegation
    ///     * request of the specified object. Object identified
    ///     * by filehandle.
    ///     */
    ///     case CLAIM_FH: /* new to v4.1 */
    ///         /* CURRENT_FH: object being delegated */
    ///         void;
    ///
    ///     /*
    ///     * Right to file based on a delegation granted
    ///     * to a previous boot instance of the client.
    ///     * File is specified by filehandle.
    ///     */
    ///     case CLAIM_DELEG_PREV_FH: /* new to v4.1 */
    ///         /* CURRENT_FH: object being delegated */
    ///         void;
    ///
    ///     /*
    ///     * Right to the file established by an open previous
    ///     * to server reboot. File identified by filehandle.
    ///     * Used during server reclaim grace period.
    ///     */
    ///     case CLAIM_PREVIOUS:
    ///         /* CURRENT_FH: object being reclaimed */
    ///         open_delegation_type4    dc_delegate_type;
    /// };
    ///
    /// struct WANT_DELEGATION4args {
    ///     uint32_t          wda_want;
    ///     deleg_claim4     wda_claim;
    /// };
    ///
    /// union WANT_DELEGATION4res switch (nfsstat4 wdr_status) {
    ///     case NFS4_OK:
    ///         open_delegation4 wdr_resok4;
    ///     default:

```

```

///         void;
/// };
///
/// struct DESTROY_CLIENTID4args {
///         clientid4         dca_clientid;
/// };
///
/// struct DESTROY_CLIENTID4res {
///         nfsstat4         dcr_status;
/// };
///
/// struct RECLAIM_COMPLETE4args {
///         /*
///         * If rca_one_fs TRUE,
///         *
///         * CURRENT_FH: object in
///         * filesystem reclaim is
///         * complete for.
///         */
///         bool         rca_one_fs;
/// };
///
/// struct RECLAIM_COMPLETE4res {
///         nfsstat4         rcr_status;
/// };
///
/// /*
/// * Operation arrays
/// */
///
/// enum nfs_opnum4 {
///     OP_ACCESS             = 3,
///     OP_CLOSE              = 4,
///     OP_COMMIT             = 5,
///     OP_CREATE             = 6,
///     OP_DELEGPURGE        = 7,
///     OP_DELEGRETURN        = 8,
///     OP_GETATTR           = 9,
///     OP_GETFH             = 10,
///     OP_LINK               = 11,
///     OP_LOCK               = 12,
///     OP_LOCKT             = 13,
///     OP_LOCKU             = 14,
///     OP_LOOKUP            = 15,
///     OP_LOOKUPP           = 16,
///     OP_NVERIFY           = 17,
///     OP_OPEN               = 18,
///     OP_OPENATTR          = 19,

```

```

/// OP_OPEN_CONFIRM          = 20, /* Mandatory not-to-implement */
/// OP_OPEN_DOWNGRADE       = 21,
/// OP_PUTFH                 = 22,
/// OP_PUTPUBFH              = 23,
/// OP_PUTROOTFH             = 24,
/// OP_READ                   = 25,
/// OP_READDIR                = 26,
/// OP_READLINK              = 27,
/// OP_REMOVE                 = 28,
/// OP_RENAME                 = 29,
/// OP_RENEW                  = 30, /* Mandatory not-to-implement */
/// OP_RESTOREFH              = 31,
/// OP_SAVEFH                 = 32,
/// OP_SECINFO                = 33,
/// OP_SETATTR                = 34,
/// OP_SETCLIENTID           = 35, /* Mandatory not-to-implement */
/// OP_SETCLIENTID_CONFIRM   = 36, /* Mandatory not-to-implement */
/// OP_VERIFY                 = 37,
/// OP_WRITE                  = 38,
/// OP_RELEASE_LOCKOWNER     = 39, /* Mandatory not-to-implement */
/// %
/// /* new operations for NFSv4.1 */
/// %
/// OP_BACKCHANNEL_CTL       = 40,
/// OP_BIND_CONN_TO_SESSION  = 41,
/// OP_EXCHANGE_ID           = 42,
/// OP_CREATE_SESSION        = 43,
/// OP_DESTROY_SESSION       = 44,
/// OP_FREE_STATEID          = 45,
/// OP_GET_DIR_DELEGATION    = 46,
/// OP_GETDEVICEINFO         = 47,
/// OP_GETDEVICELIST         = 48,
/// OP_LAYOUTCOMMIT          = 49,
/// OP_LAYOUTGET             = 50,
/// OP_LAYOUTRETURN          = 51,
/// OP_SECINFO_NO_NAME       = 52,
/// OP_SEQUENCE               = 53,
/// OP_SET_SSV                = 54,
/// OP_TEST_STATEID          = 55,
/// OP_WANT_DELEGATION       = 56,
/// OP_DESTROY_CLIENTID      = 57,
/// OP_RECLAIM_COMPLETE       = 58,
/// OP_ILLEGAL                = 10044
/// };
///
/// union nfs_argop4 switch (nfs_opnum4 argop) {
///   case OP_ACCESS:          ACCESS4args opaccess;
///   case OP_CLOSE:          CLOSE4args opclose;

```

```

/// case OP_COMMIT:      COMMIT4args opcommit;
/// case OP_CREATE:      CREATE4args opcreate;
/// case OP_DELEGPURGE:  DELEGPURGE4args opdeleGPurge;
/// case OP_DELEGRETURN: DELEGRETURN4args opdelegreturn;
/// case OP_GETATTR:     GETATTR4args opgetattr;
/// case OP_GETFH:       void;
/// case OP_LINK:        LINK4args oplink;
/// case OP_LOCK:        LOCK4args oplock;
/// case OP_LOCKT:       LOCKT4args oplockt;
/// case OP_LOCKU:       LOCKU4args oplocku;
/// case OP_LOOKUP:      LOOKUP4args oplookup;
/// case OP_LOOKUPP:     void;
/// case OP_NVERIFY:     NVERIFY4args opnverify;
/// case OP_OPEN:        OPEN4args oopen;
/// case OP_OPENATTR:    OPENATTR4args oopenattr;
///
/// /* Not for NFSv4.1 */
/// case OP_OPEN_CONFIRM: OPEN_CONFIRM4args oopen_confirm;
///
/// case OP_OPEN_DOWNGRADE:
///
/// OPEN_DOWNGRADE4args oopen_downgrade;
///
/// case OP_PUTFH:        PUTFH4args opputfh;
/// case OP_PUTPUBFH:    void;
/// case OP_PUTROOTFH:   void;
/// case OP_READ:        READ4args opread;
/// case OP_READDIR:     READDIR4args opreaddir;
/// case OP_READLINK:    void;
/// case OP_REMOVE:      REMOVE4args opremove;
/// case OP_RENAME:      RENAME4args oprename;
///
/// /* Not for NFSv4.1 */
/// case OP_RENEW:       RENEW4args oprenew;
///
/// case OP_RESTOREFH:   void;
/// case OP_SAVEFH:      void;
/// case OP_SECINFO:     SECINFO4args opsecinfo;
/// case OP_SETATTR:     SETATTR4args opsetattr;
///
/// /* Not for NFSv4.1 */
/// case OP_SETCLIENTID: SETCLIENTID4args opsetclientid;
///
/// /* Not for NFSv4.1 */
/// case OP_SETCLIENTID_CONFIRM: SETCLIENTID_CONFIRM4args
///                               opsetclientid_confirm;
/// case OP_VERIFY:      VERIFY4args opverify;
/// case OP_WRITE:       WRITE4args opwrite;
///

```

```
/// /* Not for NFSv4.1 */
/// case OP_RELEASE_LOCKOWNER:
///         RELEASE_LOCKOWNER4args
///         oprelease_lockowner;
///
/// /* Operations new to NFSv4.1 */
/// case OP_BACKCHANNEL_CTL:
///         BACKCHANNEL_CTL4args opbackchannel_ctl;
///
/// case OP_BIND_CONN_TO_SESSION:
///         BIND_CONN_TO_SESSION4args
///         opbind_conn_to_session;
///
/// case OP_EXCHANGE_ID:    EXCHANGE_ID4args opexchange_id;
///
/// case OP_CREATE_SESSION:
///         CREATE_SESSION4args opcreate_session;
///
/// case OP_DESTROY_SESSION:
///         DESTROY_SESSION4args opdestroy_session;
///
/// case OP_FREE_STATEID:  FREE_STATEID4args opfree_stateid;
///
/// case OP_GET_DIR_DELEGATION:
///         GET_DIR_DELEGATION4args
///         opget_dir_delegation;
///
/// case OP_GETDEVICEINFO: GETDEVICEINFO4args opgetdeviceinfo;
/// case OP_GETDEVICELIST: GETDEVICELIST4args opgetdevicelist;
/// case OP_LAYOUTCOMMIT:  LAYOUTCOMMIT4args oplayoutcommit;
/// case OP_LAYOUTGET:     LAYOUTGET4args oplayoutget;
/// case OP_LAYOUTRETURN:  LAYOUTRETURN4args oplayoutreturn;
///
/// case OP_SECINFO_NO_NAME:
///         SECINFO_NO_NAME4args opsecinfo_no_name;
///
/// case OP_SEQUENCE:      SEQUENCE4args opsequence;
/// case OP_SET_SSV:       SET_SSV4args opset_ssv;
/// case OP_TEST_STATEID:  TEST_STATEID4args optest_stateid;
///
/// case OP_WANT_DELEGATION:
///         WANT_DELEGATION4args opwant_delegation;
///
/// case OP_DESTROY_CLIENTID:
///         DESTROY_CLIENTID4args
///         opdestroy_clientid;
///
/// case OP_RECLAIM_COMPLETE:
```

```

///          RECLAIM_COMPLETE4args
///          opreclaim_complete;
///
/// /* Operations not new to NFSv4.1 */
/// case OP_ILLEGAL:      void;
/// };
///
/// union nfs_resop4 switch (nfs_opnum4 resop) {
/// case OP_ACCESS:      ACCESS4res opaccess;
/// case OP_CLOSE:      CLOSE4res opclose;
/// case OP_COMMIT:     COMMIT4res opcommit;
/// case OP_CREATE:     CREATE4res opcreate;
/// case OP_DELEGPURGE:  DELEGPURGE4res opdeleGPurge;
/// case OP_DELEGRETURN: DELEGRETURN4res opdelegreturn;
/// case OP_GETATTR:    GETATTR4res opgetattr;
/// case OP_GETFH:     GETFH4res opgetfh;
/// case OP_LINK:      LINK4res oplink;
/// case OP_LOCK:      LOCK4res oplock;
/// case OP_LOCKT:     LOCKT4res oplockt;
/// case OP_LOCKU:     LOCKU4res oplocku;
/// case OP_LOOKUP:    LOOKUP4res oplookup;
/// case OP_LOOKUPP:   LOOKUPP4res oplookupp;
/// case OP_NVERIFY:   NVERIFY4res opnverify;
/// case OP_OPEN:      OPEN4res opopen;
/// case OP_OPENATTR:  OPENATTR4res opopenattr;
/// /* Not for NFSv4.1 */
/// case OP_OPEN_CONFIRM: OPEN_CONFIRM4res opopen_confirm;
///
/// case OP_OPEN_DOWNGRADE:
///          OPEN_DOWNGRADE4res
///          opopen_downgrade;
///
/// case OP_PUTFH:     PUTFH4res opputfh;
/// case OP_PUTPUBFH:  PUTPUBFH4res opputpubfh;
/// case OP_PUTROOTFH: PUTROOTFH4res opputrootfh;
/// case OP_READ:      READ4res opread;
/// case OP_READDIR:   READDIR4res opreaddir;
/// case OP_READLINK:  READLINK4res opreadlink;
/// case OP_REMOVE:    REMOVE4res opremove;
/// case OP_RENAME:    RENAME4res oprename;
/// /* Not for NFSv4.1 */
/// case OP_RENEW:     RENEW4res oprenew;
/// case OP_RESTOREFH: RESTOREFH4res oprestorefh;
/// case OP_SAVEFH:    SAVEFH4res opsavefh;
/// case OP_SECINFO:   SECINFO4res opsecinfo;
/// case OP_SETATTR:   SETATTR4res opsetattr;
/// /* Not for NFSv4.1 */
/// case OP_SETCLIENTID: SETCLIENTID4res opsetclientid;

```



```

///
/// case OP_SECINFO_NO_NAME:
///         SECINFO_NO_NAME4res
///         opsecinfo_no_name;
///
/// case OP_SEQUENCE:      SEQUENCE4res opsequence;
/// case OP_SET_SSV:      SET_SSV4res opset_ssv;
/// case OP_TEST_STATEID: TEST_STATEID4res optest_stateid;
///
/// case OP_WANT_DELEGATION:
///         WANT_DELEGATION4res
///         opwant_delegation;
///
/// case OP_DESTROY_CLIENTID:
///         DESTROY_CLIENTID4res
///         opdestroy_clientid;
///
/// case OP_RECLAIM_COMPLETE:
///         RECLAIM_COMPLETE4res
///         opreclaim_complete;
///
/// /* Operations not new to NFSv4.1 */
/// case OP_ILLEGAL:      ILLEGAL4res opillegal;
/// };
///
/// struct COMPOUND4args {
///     utf8str_cs    tag;
///     uint32_t      minorversion;
///     nfs_argop4    argarray<>;
/// };
///
/// struct COMPOUND4res {
///     nfsstat4      status;
///     utf8str_cs    tag;
///     nfs_resop4    resarray<>;
/// };
///
/// /*
///  * Remote file service routines
///  */
/// program NFS4_PROGRAM {
///     version NFS_V4 {
///         void
///         NFSPROC4_NULL(void) = 0;
///
///         COMPOUND4res
///         NFSPROC4_COMPOUND(COMPOUND4args) = 1;

```

```

///
///     } = 4;
/// } = 100003;
///
/// /*
///  * NFS4 Callback Procedure Definitions and Program
///  */
/// struct CB_GETATTR4args {
///     nfs_fh4 fh;
///     bitmap4 attr_request;
/// };
///
/// struct CB_GETATTR4resok {
///     fattr4 obj_attributes;
/// };
///
/// union CB_GETATTR4res switch (nfsstat4 status) {
///     case NFS4_OK:
///         CB_GETATTR4resok     resok4;
///     default:
///         void;
/// };
///
/// struct CB_RECALL4args {
///     stateid4 stateid;
///     bool truncate;
///     nfs_fh4 fh;
/// };
///
/// struct CB_RECALL4res {
///     nfsstat4 status;
/// };
///
/// /*
///  * CB_ILLEGAL: Response for illegal operation numbers
///  */
/// struct CB_ILLEGAL4res {
///     nfsstat4 status;
/// };
///
/// /*
///  * NFSv4.1 callback arguments and results
///  */
///
/// enum layoutrecall_type4 {
///     LAYOUTRECALL4_FILE = LAYOUT4_RET_REC_FILE,
///     LAYOUTRECALL4_FSID = LAYOUT4_RET_REC_FSID,
///     LAYOUTRECALL4_ALL = LAYOUT4_RET_REC_ALL

```

```

    /// };
    ///
    /// struct layoutrecall_file4 {
    ///     nfs_fh4        lor_fh;
    ///     offset4       lor_offset;
    ///     length4        lor_length;
    ///     stateid4       lor_stateid;
    /// };
    ///
    /// union layoutrecall4 switch(layoutrecall_type4 lor_recalltype) {
    /// case LAYOUTRECALL4_FILE:
    ///     layoutrecall_file4 lor_layout;
    /// case LAYOUTRECALL4_FSID:
    ///     fsid4             lor_fsid;
    /// case LAYOUTRECALL4_ALL:
    ///     void;
    /// };
    ///
    /// struct CB_LAYOUTRECALL4args {
    ///     layouttype4     clora_type;
    ///     layoutiomode4   clora_iomode;
    ///     bool            clora_changed;
    ///     layoutrecall4   clora_recall;
    /// };
    /// struct CB_LAYOUTRECALL4res {
    ///     nfsstat4        clorr_status;
    /// };
    ///
    /// /*
    ///  * Directory notification types.
    ///  */
    /// enum notify_type4 {
    ///     NOTIFY4_CHANGE_CHILD_ATTRS = 0,
    ///     NOTIFY4_CHANGE_DIR_ATTRS = 1,
    ///     NOTIFY4_REMOVE_ENTRY = 2,
    ///     NOTIFY4_ADD_ENTRY = 3,
    ///     NOTIFY4_RENAME_ENTRY = 4,
    ///     NOTIFY4_CHANGE_COOKIE_VERIFIER = 5
    /// };
    ///
    /// /* Changed entry information. */
    /// struct notify_entry4 {
    ///     component4     ne_file;
    ///     fattr4         ne_attrs;
    /// };
    ///
    /// /* Previous entry information */
    /// struct prev_entry4 {

```

```

    ///         notify_entry4    pe_prev_entry;
    ///         /* what READDIR returned for this entry */
    ///         nfs_cookie4      pe_prev_entry_cookie;
    ///     };
    ///
    /// struct notify_remove4 {
    ///     notify_entry4    nrm_old_entry;
    ///     nfs_cookie4      nrm_old_entry_cookie;
    /// };
    ///
    /// struct notify_add4 {
    ///     /*
    ///     * Information on object
    ///     * possibly renamed over.
    ///     */
    ///     notify_remove4    nad_old_entry<1>;
    ///     notify_entry4     nad_new_entry;
    ///     /* what READDIR would have returned for this entry */
    ///     nfs_cookie4       nad_new_entry_cookie<1>;
    ///     prev_entry4       nad_prev_entry<1>;
    ///     bool               nad_last_entry;
    /// };
    ///
    /// struct notify_attr4 {
    ///     notify_entry4     na_changed_entry;
    /// };
    ///
    /// struct notify_rename4 {
    ///     notify_remove4    nrn_old_entry;
    ///     notify_add4       nrn_new_entry;
    /// };
    ///
    /// struct notify_verifier4 {
    ///     verifier4         nv_old_cookieverf;
    ///     verifier4         nv_new_cookieverf;
    /// };
    ///
    /// /*
    /// * Objects of type notify_<>4 and
    /// * notify_device_<>4 are encoded in this.
    /// */
    /// typedef opaque notifylist4<>;
    ///
    /// struct notify4 {
    ///     /* composed from notify_type4 or notify_deviceid_type4 */
    ///     bitmap4           notify_mask;
    ///     notifylist4       notify_vals;
    /// };

```

```

///
/// struct CB_NOTIFY4args {
///     stateid4    cna_stateid;
///     nfs_fh4     cna_fh;
///     notify4     cna_changes<>;
/// };
///
/// struct CB_NOTIFY4res {
///     nfsstat4    cnr_status;
/// };
///
/// struct CB_PUSH_DELEG4args {
///     nfs_fh4     cpda_fh;
///     open_delegation4 cpda_delegation;
/// };
///
/// struct CB_PUSH_DELEG4res {
///     nfsstat4    cpdr_status;
/// };
///
/// const RCA4_TYPE_MASK_RDATA_DLG          = 0;
/// const RCA4_TYPE_MASK_WDATA_DLG         = 1;
/// const RCA4_TYPE_MASK_DIR_DLG           = 2;
/// const RCA4_TYPE_MASK_FILE_LAYOUT       = 3;
/// const RCA4_TYPE_MASK_BLK_LAYOUT        = 4;
/// const RCA4_TYPE_MASK_OBJ_LAYOUT_MIN     = 8;
/// const RCA4_TYPE_MASK_OBJ_LAYOUT_MAX    = 9;
/// const RCA4_TYPE_MASK_OTHER_LAYOUT_MIN  = 12;
/// const RCA4_TYPE_MASK_OTHER_LAYOUT_MAX  = 15;
///
/// struct CB_RECALL_ANY4args {
///     uint32_t    craa_objects_to_keep;
///     bitmap4     craa_type_mask;
/// };
///
/// struct CB_RECALL_ANY4res {
///     nfsstat4    crar_status;
/// };
///
/// typedef CB_RECALL_ANY4args CB_RECALLABLE_OBJ_AVAIL4args;
///
/// struct CB_RECALLABLE_OBJ_AVAIL4res {
///     nfsstat4    croa_status;
/// };
///
/// struct CB_RECALL_SLOT4args {
///     slotid4     rsa_target_highest_slotid;

```

```

/// };
///
/// struct CB_RECALL_SLOT4res {
///     nfsstat4    rsr_status;
/// };
///
/// struct referring_call4 {
///     sequenceid4    rc_sequenceid;
///     slotid4        rc_slotid;
/// };
///
/// struct referring_call_list4 {
///     sessionid4    rcl_sessionid;
///     referring_call4 rcl_referring_calls<>;
/// };
///
/// struct CB_SEQUENCE4args {
///     sessionid4        csa_sessionid;
///     sequenceid4       csa_sequenceid;
///     slotid4           csa_slotid;
///     slotid4           csa_highest_slotid;
///     bool              csa_cachethis;
///     referring_call_list4 csa_referring_call_lists<>;
/// };
///
/// struct CB_SEQUENCE4resok {
///     sessionid4        csr_sessionid;
///     sequenceid4       csr_sequenceid;
///     slotid4           csr_slotid;
///     slotid4           csr_highest_slotid;
///     slotid4           csr_target_highest_slotid;
/// };
///
/// union CB_SEQUENCE4res switch (nfsstat4 csr_status) {
/// case NFS4_OK:
///     CB_SEQUENCE4resok    csr_resok4;
/// default:
///     void;
/// };
///
/// struct CB_WANTS_CANCELLED4args {
///     bool cwca_contended_wants_cancelled;
///     bool cwca_resourced_wants_cancelled;
/// };
///
/// struct CB_WANTS_CANCELLED4res {
///     nfsstat4        cwcr_status;
/// };

```

```

///
/// struct CB_NOTIFY_LOCK4args {
///     nfs_fh4      cnla_fh;
///     lock_owner4 cnla_lock_owner;
/// };
///
/// struct CB_NOTIFY_LOCK4res {
///     nfsstat4      cnlr_status;
/// };
///
/// /*
///  * Device notification types.
///  */
/// enum notify_deviceid_type4 {
///     NOTIFY_DEVICEID4_CHANGE = 1,
///     NOTIFY_DEVICEID4_DELETE = 2
/// };
///
/// /* For NOTIFY4_DEVICEID4_DELETE */
/// struct notify_deviceid_delete4 {
///     layouttype4      ndd_layouttype;
///     deviceid4        ndd_deviceid;
/// };
///
/// /* For NOTIFY4_DEVICEID4_CHANGE */
/// struct notify_deviceid_change4 {
///     layouttype4      ndc_layouttype;
///     deviceid4        ndc_deviceid;
///     bool              ndc_immediate;
/// };
///
/// struct CB_NOTIFY_DEVICEID4args {
///     notify4 cnda_changes<>;
/// };
///
/// struct CB_NOTIFY_DEVICEID4res {
///     nfsstat4      cndr_status;
/// };
///
/// /*
///  * Various definitions for CB_COMPOUND
///  */
/// %
/// enum nfs_cb_opnum4 {
///     OP_CB_GETATTR          = 3,
///     OP_CB_RECALL           = 4,
///     /* Callback operations new to NFSv4.1 */
///     OP_CB_LAYOUTRECALL     = 5,

```

```

///      OP_CB_NOTIFY          = 6,
///      OP_CB_PUSH_DELEG      = 7,
///      OP_CB_RECALL_ANY      = 8,
///      OP_CB_RECALLABLE_OBJ_AVAIL = 9,
///      OP_CB_RECALL_SLOT     = 10,
///      OP_CB_SEQUENCE        = 11,
///      OP_CB_WANTS_CANCELLED  = 12,
///      OP_CB_NOTIFY_LOCK     = 13,
///      OP_CB_NOTIFY_DEVICEID  = 14,
///
///      OP_CB_ILLEGAL         = 10044
/// };
///
/// union nfs_cb_argop4 switch (unsigned argop) {
///   case OP_CB_GETATTR:
///     CB_GETATTR4args      opcbgetattr;
///   case OP_CB_RECALL:
///     CB_RECALL4args       opcbrecall;
///   case OP_CB_LAYOUTRECALL:
///     CB_LAYOUTRECALL4args opcblayoutrecall;
///   case OP_CB_NOTIFY:
///     CB_NOTIFY4args       opcbnotify;
///   case OP_CB_PUSH_DELEG:
///     CB_PUSH_DELEG4args   opcbpush_deleg;
///   case OP_CB_RECALL_ANY:
///     CB_RECALL_ANY4args   opcbrecall_any;
///   case OP_CB_RECALLABLE_OBJ_AVAIL:
///     CB_RECALLABLE_OBJ_AVAIL4args opcbrecallable_obj_avail;
///   case OP_CB_RECALL_SLOT:
///     CB_RECALL_SLOT4args  opcbrecall_slot;
///   case OP_CB_SEQUENCE:
///     CB_SEQUENCE4args     opcbsequence;
///   case OP_CB_WANTS_CANCELLED:
///     CB_WANTS_CANCELLED4args opcbwants_cancelled;
///   case OP_CB_NOTIFY_LOCK:
///     CB_NOTIFY_LOCK4args  opcbnotify_lock;
///   case OP_CB_NOTIFY_DEVICEID:
///     CB_NOTIFY_DEVICEID4args opcbnotify_deviceid;
///   case OP_CB_ILLEGAL:
///     void;
/// };
///
/// union nfs_cb_resop4 switch (unsigned resop) {
///   case OP_CB_GETATTR:      CB_GETATTR4res  opcbgetattr;
///   case OP_CB_RECALL:      CB_RECALL4res   opcbrecall;
///
///   /* new NFSv4.1 operations */
///   case OP_CB_LAYOUTRECALL:
///     CB_LAYOUTRECALL4res

```

```

///                                     opcblayoutrecall;
///
/// case OP_CB_NOTIFY:      CB_NOTIFY4res   opcbnotify;
///
/// case OP_CB_PUSH_DELEG:  CB_PUSH_DELEG4res
///                                     opcbpush_deleg;
///
/// case OP_CB_RECALL_ANY:  CB_RECALL_ANY4res
///                                     opcbrecall_any;
///
/// case OP_CB_RECALLABLE_OBJ_AVAIL:
///                                     CB_RECALLABLE_OBJ_AVAIL4res
///                                     opcbrecallable_obj_avail;
///
/// case OP_CB_RECALL_SLOT:
///                                     CB_RECALL_SLOT4res
///                                     opcbrecall_slot;
///
/// case OP_CB_SEQUENCE:    CB_SEQUENCE4res  opcbsequence;
///
/// case OP_CB_WANTS_CANCELLED:
///                                     CB_WANTS_CANCELLED4res
///                                     opcbwants_cancelled;
///
/// case OP_CB_NOTIFY_LOCK:
///                                     CB_NOTIFY_LOCK4res
///                                     opcbnotify_lock;
///
/// case OP_CB_NOTIFY_DEVICEID:
///                                     CB_NOTIFY_DEVICEID4res
///                                     opcbnotify_deviceid;
///
/// /* Not new operation */
/// case OP_CB_ILLEGAL:     CB_ILLEGAL4res   opcbillegal;
/// };
///
/// struct CB_COMPOUND4args {
///     utf8str_cs    tag;
///     uint32_t      minorversion;
///     uint32_t      callback_ident;
///     nfs_cb_argop4  argarray<>;
/// };
///
/// struct CB_COMPOUND4res {
///     nfsstat4      status;
///     utf8str_cs    tag;
///     nfs_cb_resop4  resarray<>;

```

```
/// };
///
///
/// /*
///  * Program number is in the transient range since the client
///  * will assign the exact transient program number and provide
///  * that to the server via the SETCLIENTID operation.
///  */
/// program NFS4_CALLBACK {
///     version NFS_CB {
///         void
///         CB_NULL(void) = 0;
///         CB_COMPOUND4res
///         CB_COMPOUND(CB_COMPOUND4args) = 1;
///     } = 1;
/// } = 0x40000000;
```

<CODE ENDS>

3. Security Considerations

See the Security Considerations section of [4].

4. IANA Considerations

See the IANA Considerations section of [4].

5. Normative References

- [1] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [2] IETF Trust, "Legal Provisions Relating to IETF Documents", November 2008.
- [3] Eisler, M., "XDR: External Data Representation Standard", STD 67, RFC 4506, May 2006.
- [4] Shepler, S., Ed., Eisler, M., Ed., and D. Noveck, Ed., "Network File System (NFS) Version 4 Minor Version 1 Protocol", RFC 5661, January 2010.
- [5] Shepler, S., Callaghan, B., Robinson, D., Thurlow, R., Beame, C., Eisler, M., and D. Noveck, "Network File System (NFS) version 4 Protocol", RFC 3530, April 2003.

Appendix A. Acknowledgments

The authors are grateful to Lars Eggert for navigating the intellectual property issues of this document.

Authors' Addresses

Spencer Shepler (editor)
Storspeed, Inc.
7808 Moonflower Drive
Austin, TX 78750
USA

Phone: +1-512-402-5811 ext 8530
EMail: shepler@storspeed.com

Mike Eisler (editor)
NetApp
5765 Chase Point Circle
Colorado Springs, CO 80919
USA

Phone: +1-719-599-9026
EMail: mike@eisler.com

David Noveck (editor)
NetApp
1601 Trapelo Road, Suite 16
Waltham, MA 02451
USA

Phone: +1-781-768-5347
EMail: dnoveck@netapp.com