

Package ‘ddml’

June 27, 2024

Title Double/Debiased Machine Learning

Version 0.2.2

Date 2024-06-26

Description Estimate common causal parameters using double/debiased machine learning as proposed by Chernozhukov et al. (2018) <[doi:10.1111/ectj.12097](https://doi.org/10.1111/ectj.12097)>. 'ddml' simplifies estimation based on (short-)stacking as discussed in Ahrens et al. (2024) <[doi:10.1177/1536867X241233641](https://doi.org/10.1177/1536867X241233641)>, which leverages multiple base learners to increase robustness to the underlying data generating process.

License GPL (>= 3)

URL <https://github.com/thomaswiemann/ddml>,
<https://thomaswiemann.com/ddml/>

BugReports <https://github.com/thomaswiemann/ddml/issues>

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Depends R (>= 3.6)

Imports methods, stats, AER, MASS, Matrix, nnls, quadprog, glmnet,
ranger, xgboost

Suggests sandwich, covr, testthat (>= 3.0.0), knitr, rmarkdown

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Achim Ahrens [aut],
Christian B Hansen [aut],
Mark E Schaffer [aut],
Thomas Wiemann [aut, cre]

Maintainer Thomas Wiemann <wiemann@uchicago.edu>

Repository CRAN

Date/Publication 2024-06-27 00:10:02 UTC

Contents

AE98	2
crosspred	3
crossval	6
ddml	7
ddml_ate	8
ddml_fpliv	12
ddml_late	15
ddml_pliv	18
ddml_plm	21
mdl_glm	25
mdl_glmnet	25
mdl_ranger	26
mdl_xgboost	27
ols	28
print.summary.ddml_ate	29
print.summary.ddml_fpliv	30
shortstacking	31
summary.ddml_ate	33
summary.ddml_fpliv	34
Index	36

 AE98

Random subsample from the data of Angrist & Evans (1991).

Description

Random subsample from the data of Angrist & Evans (1991).

Usage

AE98

Format

A data frame with 5,000 rows and 13 variables.

worked Indicator equal to 1 if the mother is employed.

weeksw Number of weeks of employment.

hoursw Hours worked per week.

morekids Indicator equal to 1 if the mother has more than 2 kids.

samesex Indicator equal to 1 if the first two children are of the same sex.

age Age in years.

agefst Age in years at birth of the first child.

- black** Indicator equal to 1 if the mother is black.
- hisp** Indicator equal to 1 if the mother is Hispanic.
- othrace** Indicator equal to 1 if the mother is neither black nor Hispanic.
- educ** Years of education.
- boy1st** Indicator equal to 1 if the first child is male.
- boy2nd** Indicator equal to 1 if the second child is male.

Source

<https://dataverse.harvard.edu/dataset.xhtml?persistentId=hdl:1902.1/11288>

References

Angrist J, Evans W (1998). "Children and Their Parents' Labor Supply: Evidence from Exogenous Variation in Family Size." *American Economic Review*, 88(3), 450-477.

crosspred

Cross-Predictions using Stacking.

Description

Cross-predictions using stacking.

Usage

```
crosspred(  
  y,  
  X,  
  Z = NULL,  
  learners,  
  sample_folds = 2,  
  ensemble_type = "average",  
  cv_folds = 5,  
  custom_ensemble_weights = NULL,  
  compute_insample_predictions = FALSE,  
  compute_predictions_bylearner = FALSE,  
  subsamples = NULL,  
  cv_subsamples_list = NULL,  
  silent = FALSE,  
  progress = NULL,  
  auxilliary_X = NULL  
)
```

Arguments

<code>y</code>	The outcome variable.
<code>X</code>	A (sparse) matrix of predictive variables.
<code>Z</code>	Optional additional (sparse) matrix of predictive variables.
<code>learners</code>	<p>May take one of two forms, depending on whether a single learner or stacking with multiple learners is used for estimation of the predictor. If a single learner is used, <code>learners</code> is a list with two named elements:</p> <ul style="list-style-type: none"> • <code>what</code> The base learner function. The function must be such that it predicts a named input <code>y</code> using a named input <code>X</code>. • <code>args</code> Optional arguments to be passed to <code>what</code>. <p>If stacking with multiple learners is used, <code>learners</code> is a list of lists, each containing four named elements:</p> <ul style="list-style-type: none"> • <code>fun</code> The base learner function. The function must be such that it predicts a named input <code>y</code> using a named input <code>X</code>. • <code>args</code> Optional arguments to be passed to <code>fun</code>. • <code>assign_X</code> An optional vector of column indices corresponding to predictive variables in <code>X</code> that are passed to the base learner. • <code>assign_Z</code> An optional vector of column indices corresponding to predictive in <code>Z</code> that are passed to the base learner. <p>Omission of the <code>args</code> element results in default arguments being used in <code>fun</code>. Omission of <code>assign_X</code> (and/or <code>assign_Z</code>) results in inclusion of all variables in <code>X</code> (and/or <code>Z</code>).</p>
<code>sample_folds</code>	Number of cross-fitting folds.
<code>ensemble_type</code>	<p>Ensemble method to combine base learners into final estimate of the conditional expectation functions. Possible values are:</p> <ul style="list-style-type: none"> • <code>"nnls"</code> Non-negative least squares. • <code>"nnls1"</code> Non-negative least squares with the constraint that all weights sum to one. • <code>"singlebest"</code> Select base learner with minimum MSPE. • <code>"ols"</code> Ordinary least squares. • <code>"average"</code> Simple average over base learners. <p>Multiple ensemble types may be passed as a vector of strings.</p>
<code>cv_folds</code>	Number of folds used for cross-validation in ensemble construction.
<code>custom_ensemble_weights</code>	A numerical matrix with user-specified ensemble weights. Each column corresponds to a custom ensemble specification, each row corresponds to a base learner in <code>learners</code> (in chronological order). Optional column names are used to name the estimation results corresponding the custom ensemble specification.
<code>compute_insample_predictions</code>	Indicator equal to 1 if in-sample predictions should also be computed.
<code>compute_predictions_bylearner</code>	Indicator equal to 1 if in-sample predictions should also be computed for each learner (rather than the entire ensemble).

subsamples	List of vectors with sample indices for cross-fitting.
cv_subsamples_list	List of lists, each corresponding to a subsample containing vectors with subsample indices for cross-validation.
silent	Boolean to silence estimation updates.
progress	String to print before learner and cv fold progress.
auxilliary_X	An optional list of matrices of length <code>sample_folds</code> , each containing additional observations to calculate predictions for.

Value

`crosspred` returns a list containing the following components:

<code>oos_fitted</code>	A matrix of out-of-sample predictions, each column corresponding to an ensemble type (in chronological order).
<code>weights</code>	An array, providing the weight assigned to each base learner (in chronological order) by the ensemble procedures.
<code>is_fitted</code>	When <code>compute_insample_predictions = T</code> , a list of matrices with in-sample predictions by sample fold.
<code>auxilliary_fitted</code>	When <code>auxilliary_X</code> is not <code>NULL</code> , a list of matrices with additional predictions.
<code>oos_fitted_bylearner</code>	When <code>compute_predictions_bylearner = T</code> , a matrix of out-of-sample predictions, each column corresponding to a base learner (in chronological order).
<code>is_fitted_bylearner</code>	When <code>compute_insample_predictions = T</code> and <code>compute_predictions_bylearner = T</code> , a list of matrices with in-sample predictions by sample fold.
<code>auxilliary_fitted_bylearner</code>	When <code>auxilliary_X</code> is not <code>NULL</code> and <code>compute_predictions_bylearner = T</code> , a list of matrices with additional predictions for each learner.

References

- Ahrens A, Hansen C B, Schaffer M E, Wiemann T (2023). "ddml: Double/debiased machine learning in Stata." <https://arxiv.org/abs/2301.09397>
- Wolpert D H (1992). "Stacked generalization." *Neural Networks*, 5(2), 241-259.

See Also

Other utilities: [crossval\(\)](#), [shortstacking\(\)](#)

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
X = AE98[, c("morekids", "age", "agefst", "black", "hispanic", "othrace", "educ")]

# Compute cross-predictions using stacking with base learners ols and lasso.
# Two stacking approaches are simultaneously computed: Equally
# weighted (ensemble_type = "average") and MSPE-minimizing with weights
```

```

#   in the unit simplex (ensemble_type = "nnls1"). Predictions for each
#   learner are also calculated.
crosspred_res <- crosspred(y, X,
                          learners = list(list(fun = ols),
                                           list(fun = mdl_glmnet)),
                          ensemble_type = c("average",
                                           "nnls1",
                                           "singlebest"),
                          compute_predictions_bylearner = TRUE,
                          sample_folds = 2,
                          cv_folds = 2,
                          silent = TRUE)
dim(crosspred_res$oos_fitted) # = length(y) by length(ensemble_type)
dim(crosspred_res$oos_fitted_bylearner) # = length(y) by length(learners)

```

crossval	<i>Estimator of the Mean Squared Prediction Error using Cross-Validation.</i>
----------	---

Description

Estimator of the mean squared prediction error of different learners using cross-validation.

Usage

```

crossval(
  y,
  X,
  Z = NULL,
  learners,
  cv_folds = 5,
  cv_subsamples = NULL,
  silent = FALSE,
  progress = NULL
)

```

Arguments

y	The outcome variable.
X	A (sparse) matrix of predictive variables.
Z	Optional additional (sparse) matrix of predictive variables.
learners	learners is a list of lists, each containing four named elements: <ul style="list-style-type: none"> • fun The base learner function. The function must be such that it predicts a named input y using a named input X. • args Optional arguments to be passed to fun. • assign_X An optional vector of column indices corresponding to variables in X that are passed to the base learner.

- `assign_Z` An optional vector of column indices corresponding to variables in `Z` that are passed to the base learner.

Omission of the `args` element results in default arguments being used in `fun`. Omission of `assign_X` (and/or `assign_Z`) results in inclusion of all predictive variables in `X` (and/or `Z`).

<code>cv_folds</code>	Number of folds used for cross-validation.
<code>cv_subsamples</code>	List of vectors with sample indices for cross-validation.
<code>silent</code>	Boolean to silence estimation updates.
<code>progress</code>	String to print before learner and <code>cv</code> fold progress.

Value

`crossval` returns a list containing the following components:

- `mspe` A vector of MSPE estimates, each corresponding to a base learners (in chronological order).
- `oos_resid` A matrix of out-of-sample prediction errors, each column corresponding to a base learners (in chronological order).
- `cv_subsamples` Pass-through of `cv_subsamples`. See above.

See Also

Other utilities: [crosspred\(\)](#), [shortstacking\(\)](#)

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
X = AE98[, c("morekids", "age", "agefst", "black", "hispanic", "othrace", "educ")]

# Compare ols, lasso, and ridge using 4-fold cross-validation
cv_res <- crossval(y, X,
  learners = list(list(fun = ols),
                  list(fun = mdl_glmnet),
                  list(fun = mdl_glmnet,
                      args = list(alpha = 0))),
  cv_folds = 4,
  silent = TRUE)

cv_res$mspe
```

Description

Estimate common causal parameters using double/debiased machine learning as proposed by Chernozhukov et al. (2018). `'ddml'` simplifies estimation based on (short-)stacking, which leverages multiple base learners to increase robustness to the underlying data generating process.

References

Chernozhukov V, Chetverikov D, Demirer M, Duflo E, Hansen C B, Newey W, Robins J (2018). "Double/debiased machine learning for treatment and structural parameters." *The Econometrics Journal*, 21(1), C1-C68.

ddml_ate	<i>Estimators of Average Treatment Effects.</i>
----------	---

Description

Estimators of the average treatment effect and the average treatment effect on the treated.

Usage

```
ddml_ate(
  y,
  D,
  X,
  learners,
  learners_DX = learners,
  sample_folds = 2,
  ensemble_type = "nnls",
  shortstack = FALSE,
  cv_folds = 5,
  custom_ensemble_weights = NULL,
  custom_ensemble_weights_DX = custom_ensemble_weights,
  subsamples_D0 = NULL,
  subsamples_D1 = NULL,
  cv_subsamples_list_D0 = NULL,
  cv_subsamples_list_D1 = NULL,
  trim = 0.01,
  silent = FALSE
)

ddml_att(
  y,
  D,
  X,
  learners,
  learners_DX = learners,
  sample_folds = 2,
  ensemble_type = "nnls",
  shortstack = FALSE,
  cv_folds = 5,
  custom_ensemble_weights = NULL,
  custom_ensemble_weights_DX = custom_ensemble_weights,
```



```

    subsamples_D0 = NULL,
    subsamples_D1 = NULL,
    cv_subsamples_list_D0 = NULL,
    cv_subsamples_list_D1 = NULL,
    trim = 0.01,
    silent = FALSE
)

```

Arguments

<code>y</code>	The outcome variable.
<code>D</code>	The binary endogenous variable of interest.
<code>X</code>	A (sparse) matrix of control variables.
<code>learners</code>	<p>May take one of two forms, depending on whether a single learner or stacking with multiple learners is used for estimation of the conditional expectation functions. If a single learner is used, <code>learners</code> is a list with two named elements:</p> <ul style="list-style-type: none"> • <code>what</code> The base learner function. The function must be such that it predicts a named input <code>y</code> using a named input <code>X</code>. • <code>args</code> Optional arguments to be passed to <code>what</code>. <p>If stacking with multiple learners is used, <code>learners</code> is a list of lists, each containing four named elements:</p> <ul style="list-style-type: none"> • <code>fun</code> The base learner function. The function must be such that it predicts a named input <code>y</code> using a named input <code>X</code>. • <code>args</code> Optional arguments to be passed to <code>fun</code>. • <code>assign_X</code> An optional vector of column indices corresponding to control variables in <code>X</code> that are passed to the base learner. <p>Omission of the <code>args</code> element results in default arguments being used in <code>fun</code>. Omission of <code>assign_X</code> results in inclusion of all variables in <code>X</code>.</p>
<code>learners_DX</code>	Optional argument to allow for different estimators of $E[D X]$. Setup is identical to <code>learners</code> .
<code>sample_folds</code>	Number of cross-fitting folds.
<code>ensemble_type</code>	<p>Ensemble method to combine base learners into final estimate of the conditional expectation functions. Possible values are:</p> <ul style="list-style-type: none"> • <code>"nnls"</code> Non-negative least squares. • <code>"nnls1"</code> Non-negative least squares with the constraint that all weights sum to one. • <code>"singlebest"</code> Select base learner with minimum MSPE. • <code>"ols"</code> Ordinary least squares. • <code>"average"</code> Simple average over base learners. <p>Multiple ensemble types may be passed as a vector of strings.</p>
<code>shortstack</code>	Boolean to use short-stacking.
<code>cv_folds</code>	Number of folds used for cross-validation in ensemble construction.

<code>custom_ensemble_weights</code>	A numerical matrix with user-specified ensemble weights. Each column corresponds to a custom ensemble specification, each row corresponds to a base learner in <code>learners</code> (in chronological order). Optional column names are used to name the estimation results corresponding the custom ensemble specification.
<code>custom_ensemble_weights_DX</code>	Optional argument to allow for different custom ensemble weights for <code>learners_DX</code> . Setup is identical to <code>custom_ensemble_weights</code> . Note: <code>custom_ensemble_weights</code> and <code>custom_ensemble_weights_DX</code> must have the same number of columns.
<code>subsamples_D0</code> , <code>subsamples_D1</code>	List of vectors with sample indices for cross-fitting, corresponding to untreated and treated observations, respectively.
<code>cv_subsamples_list_D0</code> , <code>cv_subsamples_list_D1</code>	List of lists, each corresponding to a subsample containing vectors with subsample indices for cross-validation. Arguments are separated for untreated and treated observations, respectively.
<code>trim</code>	Number in $(0, 1)$ for trimming the estimated propensity scores at <code>trim</code> and $1 - \text{trim}$.
<code>silent</code>	Boolean to silence estimation updates.

Details

`ddml_ate` and `ddml_att` provide double/debiased machine learning estimators for the average treatment effect and the average treatment effect on the treated, respectively, in the interactive model given by

$$Y = g_0(D, X) + U,$$

where (Y, D, X, U) is a random vector such that $\text{supp } D = \{0, 1\}$, $E[U|D, X] = 0$, and $\Pr(D = 1|X) \in (0, 1)$ with probability 1, and g_0 is an unknown nuisance function.

In this model, the average treatment effect is defined as

$$\theta_0^{\text{ATE}} \equiv E[g_0(1, X) - g_0(0, X)].$$

and the average treatment effect on the treated is defined as

$$\theta_0^{\text{ATT}} \equiv E[g_0(1, X) - g_0(0, X)|D = 1].$$

Value

`ddml_ate` and `ddml_att` return an object of S3 class `ddml_ate` and `ddml_att`, respectively. An object of class `ddml_ate` or `ddml_att` is a list containing the following components:

- `ate / att` A vector with the average treatment effect / average treatment effect on the treated estimates.
- `weights` A list of matrices, providing the weight assigned to each base learner (in chronological order) by the ensemble procedure.
- `mspe` A list of matrices, providing the MSPE of each base learner (in chronological order) computed by the cross-validation step in the ensemble construction.
- `psi_a`, `psi_b` Matrices needed for the computation of scores. Used in `summary.ddml_ate()` or `summary.ddml_att()`.

oos_pred List of matrices, providing the reduced form predicted values.

learners,learners_DX, subsamples_D0,subsamples_D1, cv_subsamples_list_D0,cv_subsamples_list_D1, ensemble_weights
Pass-through of selected user-provided arguments. See above.

References

Ahrens A, Hansen C B, Schaffer M E, Wiemann T (2023). "ddml: Double/debiased machine learning in Stata." <https://arxiv.org/abs/2301.09397>

Chernozhukov V, Chetverikov D, Demirer M, Duflo E, Hansen C B, Newey W, Robins J (2018). "Double/debiased machine learning for treatment and structural parameters." The Econometrics Journal, 21(1), C1-C68.

Wolpert D H (1992). "Stacked generalization." Neural Networks, 5(2), 241-259.

See Also

[summary.ddml_ate\(\)](#), [summary.ddml_att\(\)](#)

Other ddml: [ddml_fpliv\(\)](#), [ddml_late\(\)](#), [ddml_pliv\(\)](#), [ddml_plm\(\)](#)

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
D = AE98[, "morekids"]
X = AE98[, c("age", "agefst", "black", "hispanic", "othrace", "educ")]

# Estimate the average treatment effect using a single base learner, ridge.
ate_fit <- ddml_ate(y, D, X,
  learners = list(what = mdl_glmnet,
    args = list(alpha = 0)),
  sample_folds = 2,
  silent = TRUE)
summary(ate_fit)

# Estimate the average treatment effect using short-stacking with base
# learners ols, lasso, and ridge. We can also use custom_ensemble_weights
# to estimate the ATE using every individual base learner.
weights_everylearner <- diag(1, 3)
colnames(weights_everylearner) <- c("mdl:ols", "mdl:lasso", "mdl:ridge")
ate_fit <- ddml_ate(y, D, X,
  learners = list(list(fun = ols),
    list(fun = mdl_glmnet),
    list(fun = mdl_glmnet,
      args = list(alpha = 0))),
  ensemble_type = 'nnls',
  custom_ensemble_weights = weights_everylearner,
  shortstack = TRUE,
  sample_folds = 2,
  silent = TRUE)
summary(ate_fit)
```

ddml_fpliv

*Estimator for the Flexible Partially Linear IV Model.***Description**

Estimator for the flexible partially linear IV model.

Usage

```
ddml_fpliv(
  y,
  D,
  Z,
  X,
  learners,
  learners_DXZ = learners,
  learners_DX = learners,
  sample_folds = 2,
  ensemble_type = "nnls",
  shortstack = FALSE,
  cv_folds = 5,
  enforce_LIE = TRUE,
  custom_ensemble_weights = NULL,
  custom_ensemble_weights_DXZ = custom_ensemble_weights,
  custom_ensemble_weights_DX = custom_ensemble_weights,
  subsamples = NULL,
  cv_subsamples_list = NULL,
  silent = FALSE
)
```

Arguments

y	The outcome variable.
D	A matrix of endogenous variables.
Z	A (sparse) matrix of instruments.
X	A (sparse) matrix of control variables.
learners	<p>May take one of two forms, depending on whether a single learner or stacking with multiple learners is used for estimation of the conditional expectation functions. If a single learner is used, learners is a list with two named elements:</p> <ul style="list-style-type: none"> • what The base learner function. The function must be such that it predicts a named input y using a named input X. • args Optional arguments to be passed to what. <p>If stacking with multiple learners is used, learners is a list of lists, each containing four named elements:</p>

- `fun` The base learner function. The function must be such that it predicts a named input `y` using a named input `X`.
- `args` Optional arguments to be passed to `fun`.
- `assign_X` An optional vector of column indices corresponding to control variables in `X` that are passed to the base learner.
- `assign_Z` An optional vector of column indices corresponding to instruments in `Z` that are passed to the base learner.

Omission of the `args` element results in default arguments being used in `fun`. Omission of `assign_X` (and/or `assign_Z`) results in inclusion of all variables in `X` (and/or `Z`).

`learners_DXZ`, `learners_DX`

Optional arguments to allow for different estimators of $E[D|X, Z]$, $E[D|X]$. Setup is identical to `learners`.

`sample_folds` Number of cross-fitting folds.

`ensemble_type` Ensemble method to combine base learners into final estimate of the conditional expectation functions. Possible values are:

- `"npls"` Non-negative least squares.
- `"npls1"` Non-negative least squares with the constraint that all weights sum to one.
- `"singlebest"` Select base learner with minimum MSPE.
- `"ols"` Ordinary least squares.
- `"average"` Simple average over base learners.

Multiple ensemble types may be passed as a vector of strings.

`shortstack` Boolean to use short-stacking.

`cv_folds` Number of folds used for cross-validation in ensemble construction.

`enforce_LIE` Indicator equal to 1 if the law of iterated expectations is enforced in the first stage.

`custom_ensemble_weights`

A numerical matrix with user-specified ensemble weights. Each column corresponds to a custom ensemble specification, each row corresponds to a base learner in `learners` (in chronological order). Optional column names are used to name the estimation results corresponding the custom ensemble specification.

`custom_ensemble_weights_DXZ`, `custom_ensemble_weights_DX`

Optional arguments to allow for different custom ensemble weights for `learners_DXZ`, `learners_DX`. Setup is identical to `custom_ensemble_weights`. Note: `custom_ensemble_weights` and `custom_ensemble_weights_DXZ`, `custom_ensemble_weights_DX` must have the same number of columns.

`subsamples` List of vectors with sample indices for cross-fitting.

`cv_subsamples_list`

List of lists, each corresponding to a subsample containing vectors with subsample indices for cross-validation.

`silent` Boolean to silence estimation updates.


```

                                args = list(alpha = 0)),
                                sample_folds = 2,
                                silent = TRUE)
summary(fpliv_fit)

```

ddml_ate

Estimator of the Local Average Treatment Effect.

Description

Estimator of the local average treatment effect.

Usage

```

ddml_ate(
  y,
  D,
  Z,
  X,
  learners,
  learners_DXZ = learners,
  learners_ZX = learners,
  sample_folds = 2,
  ensemble_type = "nnls",
  shortstack = FALSE,
  cv_folds = 5,
  custom_ensemble_weights = NULL,
  custom_ensemble_weights_DXZ = custom_ensemble_weights,
  custom_ensemble_weights_ZX = custom_ensemble_weights,
  subsamples_Z0 = NULL,
  subsamples_Z1 = NULL,
  cv_subsamples_list_Z0 = NULL,
  cv_subsamples_list_Z1 = NULL,
  trim = 0.01,
  silent = FALSE
)

```

Arguments

y	The outcome variable.
D	The binary endogenous variable of interest.
Z	Binary instrumental variable.
X	A (sparse) matrix of control variables.
learners	May take one of two forms, depending on whether a single learner or stacking with multiple learners is used for estimation of the conditional expectation functions. If a single learner is used, learners is a list with two named elements:

- `what` The base learner function. The function must be such that it predicts a named input `y` using a named input `X`.
- `args` Optional arguments to be passed to `what`.

If stacking with multiple learners is used, `learners` is a list of lists, each containing four named elements:

- `fun` The base learner function. The function must be such that it predicts a named input `y` using a named input `X`.
- `args` Optional arguments to be passed to `fun`.
- `assign_X` An optional vector of column indices corresponding to control variables in `X` that are passed to the base learner.
- `assign_Z` An optional vector of column indices corresponding to instruments in `Z` that are passed to the base learner.

Omission of the `args` element results in default arguments being used in `fun`. Omission of `assign_X` (and/or `assign_Z`) results in inclusion of all variables in `X` (and/or `Z`).

`learners_DXZ`, `learners_ZX`

Optional arguments to allow for different estimators of $E[D|X, Z]$, $E[Z|X]$. Setup is identical to `learners`.

`sample_folds` Number of cross-fitting folds.

`ensemble_type` Ensemble method to combine base learners into final estimate of the conditional expectation functions. Possible values are:

- `"nnls"` Non-negative least squares.
- `"nnls1"` Non-negative least squares with the constraint that all weights sum to one.
- `"singlebest"` Select base learner with minimum MSPE.
- `"ols"` Ordinary least squares.
- `"average"` Simple average over base learners.

Multiple ensemble types may be passed as a vector of strings.

`shortstack` Boolean to use short-stacking.

`cv_folds` Number of folds used for cross-validation in ensemble construction.

`custom_ensemble_weights`

A numerical matrix with user-specified ensemble weights. Each column corresponds to a custom ensemble specification, each row corresponds to a base learner in `learners` (in chronological order). Optional column names are used to name the estimation results corresponding the custom ensemble specification.

`custom_ensemble_weights_DXZ`, `custom_ensemble_weights_ZX`

Optional arguments to allow for different custom ensemble weights for `learners_DXZ`, `learners_ZX`. Setup is identical to `custom_ensemble_weights`. Note: `custom_ensemble_weights` and `custom_ensemble_weights_DXZ`, `custom_ensemble_weights_ZX` must have the same number of columns.

`subsamples_Z0`, `subsamples_Z1`

List of vectors with sample indices for cross-fitting, corresponding to observations with $Z = 0$ and $Z = 1$, respectively.

cv_subsamples_list_Z0, cv_subsamples_list_Z1	List of lists, each corresponding to a subsample containing vectors with subsample indices for cross-validation. Arguments are separated for observations with $Z = 0$ and $Z = 1$, respectively.
trim	Number in $(0, 1)$ for trimming the estimated propensity scores at trim and $1 - \text{trim}$.
silent	Boolean to silence estimation updates.

Details

ddml_ate provides a double/debiased machine learning estimator for the local average treatment effect in the interactive model given by

$$Y = g_0(D, X) + U,$$

where (Y, D, X, Z, U) is a random vector such that $\text{supp } D = \text{supp } Z = \{0, 1\}$, $E[U|X, Z] = 0$, $E[\text{Var}(E[D|X, Z]|X)] \neq 0$, $\Pr(Z = 1|X) \in (0, 1)$ with probability 1, $p_0(1, X) \geq p_0(0, X)$ with probability 1 where $p_0(Z, X) \equiv \Pr(D = 1|Z, X)$, and g_0 is an unknown nuisance function.

In this model, the local average treatment effect is defined as

$$\theta_0^{\text{LATE}} \equiv E[g_0(1, X) - g_0(0, X) | p_0(1, X) > p_0(0, X)].$$

Value

ddml_ate returns an object of S3 class ddml_ate. An object of class ddml_ate is a list containing the following components:

late A vector with the average treatment effect estimates.

weights A list of matrices, providing the weight assigned to each base learner (in chronological order) by the ensemble procedure.

mspe A list of matrices, providing the MSPE of each base learner (in chronological order) computed by the cross-validation step in the ensemble construction.

psi_a, psi_b Matrices needed for the computation of scores. Used in `summary.ddml_ate()`.

oos_pred List of matrices, providing the reduced form predicted values.

learners, learners_DXZ, learners_ZX, subsamples_Z0, subsamples_Z1, cv_subsamples_list_Z0, cv_subsamples_list_Z1
Pass-through of selected user-provided arguments. See above.

References

Ahrens A, Hansen C B, Schaffer M E, Wiemann T (2023). "ddml: Double/debiased machine learning in Stata." <https://arxiv.org/abs/2301.09397>

Chernozhukov V, Chetverikov D, Demirem M, Duflo E, Hansen C B, Newey W, Robins J (2018). "Double/debiased machine learning for treatment and structural parameters." *The Econometrics Journal*, 21(1), C1-C68.

Imbens G, Angrist J (1994). "Identification and Estimation of Local Average Treatment Effects." *Econometrica*, 62(2), 467-475.

Wolpert D H (1992). "Stacked generalization." *Neural Networks*, 5(2), 241-259.

See Also

[summary.ddml_late\(\)](#)

Other ddml: [ddml_ate\(\)](#), [ddml_fpliv\(\)](#), [ddml_pliv\(\)](#), [ddml_plm\(\)](#)

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
D = AE98[, "morekids"]
Z = AE98[, "samesex"]
X = AE98[, c("age", "agefst", "black", "hisp", "othrace", "educ")]

# Estimate the local average treatment effect using a single base learner,
#   ridge.
late_fit <- ddml_late(y, D, Z, X,
                    learners = list(what = mdl_glmnet,
                                   args = list(alpha = 0)),
                    sample_folds = 2,
                    silent = TRUE)
summary(late_fit)

# Estimate the local average treatment effect using short-stacking with base
#   learners ols, lasso, and ridge. We can also use custom_ensemble_weights
#   to estimate the ATE using every individual base learner.
weights_everylearner <- diag(1, 3)
colnames(weights_everylearner) <- c("mdl:ols", "mdl:lasso", "mdl:ridge")
late_fit <- ddml_late(y, D, Z, X,
                    learners = list(list(fun = ols,
                                       list(fun = mdl_glmnet),
                                       list(fun = mdl_glmnet,
                                             args = list(alpha = 0))),
                                   ensemble_type = 'nnls',
                                   custom_ensemble_weights = weights_everylearner,
                                   shortstack = TRUE,
                                   sample_folds = 2,
                                   silent = TRUE)
summary(late_fit)
```

ddml_pliv

Estimator for the Partially Linear IV Model.

Description

Estimator for the partially linear IV model.

Usage

```
ddml_pliv(
  y,
```

```

D,
Z,
X,
learners,
learners_DX = learners,
learners_ZX = learners,
sample_folds = 2,
ensemble_type = "nnls",
shortstack = FALSE,
cv_folds = 5,
custom_ensemble_weights = NULL,
custom_ensemble_weights_DX = custom_ensemble_weights,
custom_ensemble_weights_ZX = custom_ensemble_weights,
subsamples = NULL,
cv_subsamples_list = NULL,
silent = FALSE
)

```

Arguments

y	The outcome variable.
D	A matrix of endogenous variables.
Z	A matrix of instruments.
X	A (sparse) matrix of control variables.
learners	<p>May take one of two forms, depending on whether a single learner or stacking with multiple learners is used for estimation of the conditional expectation functions. If a single learner is used, learners is a list with two named elements:</p> <ul style="list-style-type: none"> • what The base learner function. The function must be such that it predicts a named input y using a named input X. • args Optional arguments to be passed to what. <p>If stacking with multiple learners is used, learners is a list of lists, each containing four named elements:</p> <ul style="list-style-type: none"> • fun The base learner function. The function must be such that it predicts a named input y using a named input X. • args Optional arguments to be passed to fun. • assign_X An optional vector of column indices corresponding to control variables in X that are passed to the base learner. • assign_Z An optional vector of column indices corresponding to instruments in Z that are passed to the base learner. <p>Omission of the args element results in default arguments being used in fun. Omission of assign_X (and/or assign_Z) results in inclusion of all variables in X (and/or Z).</p>
learners_DX, learners_ZX	Optional arguments to allow for different base learners for estimation of $E[D X]$, $E[Z X]$. Setup is identical to learners.

sample_folds	Number of cross-fitting folds.
ensemble_type	Ensemble method to combine base learners into final estimate of the conditional expectation functions. Possible values are: <ul style="list-style-type: none"> • "nnls" Non-negative least squares. • "nnls1" Non-negative least squares with the constraint that all weights sum to one. • "singlebest" Select base learner with minimum MSPE. • "ols" Ordinary least squares. • "average" Simple average over base learners. Multiple ensemble types may be passed as a vector of strings.
shortstack	Boolean to use short-stacking.
cv_folds	Number of folds used for cross-validation in ensemble construction.
custom_ensemble_weights	A numerical matrix with user-specified ensemble weights. Each column corresponds to a custom ensemble specification, each row corresponds to a base learner in learners (in chronological order). Optional column names are used to name the estimation results corresponding the custom ensemble specification.
custom_ensemble_weights_DX, custom_ensemble_weights_ZX	Optional arguments to allow for different custom ensemble weights for learners_DX, learners_ZX. Setup is identical to custom_ensemble_weights. Note: custom_ensemble_weights and custom_ensemble_weights_DX, custom_ensemble_weights_ZX must have the same number of columns.
subsamples	List of vectors with sample indices for cross-fitting.
cv_subsamples_list	List of lists, each corresponding to a subsample containing vectors with subsample indices for cross-validation.
silent	Boolean to silence estimation updates.

Details

ddml_pliv provides a double/debiased machine learning estimator for the parameter of interest θ_0 in the partially linear IV model given by

$$Y = \theta_0 D + g_0(X) + U,$$

where (Y, D, X, Z, U) is a random vector such that $E[Cov(U, Z|X)] = 0$ and $E[Cov(D, Z|X)] \neq 0$, and g_0 is an unknown nuisance function.

Value

ddml_pliv returns an object of S3 class ddml_pliv. An object of class ddml_pliv is a list containing the following components:

coef A vector with the θ_0 estimates.

weights A list of matrices, providing the weight assigned to each base learner (in chronological order) by the ensemble procedure.

- `mspe` A list of matrices, providing the MSPE of each base learner (in chronological order) computed by the cross-validation step in the ensemble construction.
- `iv_fit` Object of class `ivreg` from the IV regression of $Y - \hat{E}[Y|X]$ on $D - \hat{E}[D|X]$ using $Z - \hat{E}[Z|X]$ as the instrument. See also `AER::ivreg()` for details.
- `learners,learners_DX,learners_ZX, subsamples,cv_subsamples_list,ensemble_type` Pass-through of selected user-provided arguments. See above.

References

- Ahrens A, Hansen C B, Schaffer M E, Wiemann T (2023). "ddml: Double/debiased machine learning in Stata." <https://arxiv.org/abs/2301.09397>
- Chernozhukov V, Chetverikov D, Demirer M, Duflo E, Hansen C B, Newey W, Robins J (2018). "Double/debiased machine learning for treatment and structural parameters." *The Econometrics Journal*, 21(1), C1-C68.
- Kleibler C, Zeileis A (2008). *Applied Econometrics with R*. Springer-Verlag, New York.
- Wolpert D H (1992). "Stacked generalization." *Neural Networks*, 5(2), 241-259.

See Also

- `summary.ddml_pliv()`, `AER::ivreg()`
- Other ddml: `ddml_ate()`, `ddml_fpliv()`, `ddml_late()`, `ddml_plm()`

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
D = AE98[, "morekids"]
Z = AE98[, "samesex"]
X = AE98[, c("age", "agefst", "black", "hisp", "othrace", "educ")]

# Estimate the partially linear IV model using a single base learner, ridge.
pliv_fit <- ddml_pliv(y, D, Z, X,
  learners = list(what = mdl_glmnet,
    args = list(alpha = 0)),
  sample_folds = 2,
  silent = TRUE)

summary(pliv_fit)
```

ddml_plm

Estimator for the Partially Linear Model.

Description

Estimator for the partially linear model.

Usage

```
ddml_plm(
  y,
  D,
  X,
  learners,
  learners_DX = learners,
  sample_folds = 2,
  ensemble_type = "nnls",
  shortstack = FALSE,
  cv_folds = 5,
  custom_ensemble_weights = NULL,
  custom_ensemble_weights_DX = custom_ensemble_weights,
  subsamples = NULL,
  cv_subsamples_list = NULL,
  silent = FALSE
)
```

Arguments

y	The outcome variable.
D	A matrix of endogenous variables.
X	A (sparse) matrix of control variables.
learners	<p>May take one of two forms, depending on whether a single learner or stacking with multiple learners is used for estimation of the conditional expectation functions. If a single learner is used, learners is a list with two named elements:</p> <ul style="list-style-type: none"> • what The base learner function. The function must be such that it predicts a named input y using a named input X. • args Optional arguments to be passed to what. <p>If stacking with multiple learners is used, learners is a list of lists, each containing four named elements:</p> <ul style="list-style-type: none"> • fun The base learner function. The function must be such that it predicts a named input y using a named input X. • args Optional arguments to be passed to fun. • assign_X An optional vector of column indices corresponding to control variables in X that are passed to the base learner. <p>Omission of the args element results in default arguments being used in fun. Omission of assign_X results in inclusion of all variables in X.</p>
learners_DX	Optional argument to allow for different estimators of $E[D X]$. Setup is identical to learners.
sample_folds	Number of cross-fitting folds.
ensemble_type	<p>Ensemble method to combine base learners into final estimate of the conditional expectation functions. Possible values are:</p> <ul style="list-style-type: none"> • "nnls" Non-negative least squares.

- "nnls1" Non-negative least squares with the constraint that all weights sum to one.
- "singlebest" Select base learner with minimum MSPE.
- "ols" Ordinary least squares.
- "average" Simple average over base learners.

Multiple ensemble types may be passed as a vector of strings.

shortstack	Boolean to use short-stacking.
cv_folds	Number of folds used for cross-validation in ensemble construction.
custom_ensemble_weights	A numerical matrix with user-specified ensemble weights. Each column corresponds to a custom ensemble specification, each row corresponds to a base learner in learners (in chronological order). Optional column names are used to name the estimation results corresponding the custom ensemble specification.
custom_ensemble_weights_DX	Optional argument to allow for different custom ensemble weights for learners_DX. Setup is identical to custom_ensemble_weights. Note: custom_ensemble_weights and custom_ensemble_weights_DX must have the same number of columns.
subsamples	List of vectors with sample indices for cross-fitting.
cv_subsamples_list	List of lists, each corresponding to a subsample containing vectors with subsample indices for cross-validation.
silent	Boolean to silence estimation updates.

Details

ddml_plm provides a double/debiased machine learning estimator for the parameter of interest θ_0 in the partially linear model given by

$$Y = \theta_0 D + g_0(X) + U,$$

where (Y, D, X, U) is a random vector such that $E[Cov(U, D|X)] = 0$ and $E[Var(D|X)] \neq 0$, and g_0 is an unknown nuisance function.

Value

ddml_plm returns an object of S3 class ddm1_plm. An object of class ddm1_plm is a list containing the following components:

coef	A vector with the θ_0 estimates.
weights	A list of matrices, providing the weight assigned to each base learner (in chronological order) by the ensemble procedure.
mspe	A list of matrices, providing the MSPE of each base learner (in chronological order) computed by the cross-validation step in the ensemble construction.
ols_fit	Object of class lm from the second stage regression of $Y - \hat{E}[Y X]$ on $D - \hat{E}[D X]$.
learners, learners_DX, subsamples, cv_subsamples_list, ensemble_type	Pass-through of selected user-provided arguments. See above.

References

Ahrens A, Hansen C B, Schaffer M E, Wiemann T (2023). "ddml: Double/debiased machine learning in Stata." <https://arxiv.org/abs/2301.09397>

Chernozhukov V, Chetverikov D, Demirer M, Duflo E, Hansen C B, Newey W, Robins J (2018). "Double/debiased machine learning for treatment and structural parameters." *The Econometrics Journal*, 21(1), C1-C68.

Wolpert D H (1992). "Stacked generalization." *Neural Networks*, 5(2), 241-259.

See Also

[summary.ddml_plm\(\)](#)

Other ddml: [ddml_ate\(\)](#), [ddml_fpliv\(\)](#), [ddml_late\(\)](#), [ddml_pliv\(\)](#)

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
D = AE98[, "morekids"]
X = AE98[, c("age", "agefst", "black", "hisp", "othrace", "educ")]

# Estimate the partially linear model using a single base learner, ridge.
plm_fit <- ddml_plm(y, D, X,
  learners = list(what = mdl_glmnet,
    args = list(alpha = 0)),
  sample_folds = 2,
  silent = TRUE)
summary(plm_fit)

# Estimate the partially linear model using short-stacking with base learners
#   ols, lasso, and ridge. We can also use custom_ensemble_weights
#   to estimate the ATE using every individual base learner.
weights_everylearner <- diag(1, 3)
colnames(weights_everylearner) <- c("mdl:ols", "mdl:lasso", "mdl:ridge")
plm_fit <- ddml_plm(y, D, X,
  learners = list(list(fun = ols),
    list(fun = mdl_glmnet),
    list(fun = mdl_glmnet,
      args = list(alpha = 0))),
  ensemble_type = 'nnls',
  custom_ensemble_weights = weights_everylearner,
  shortstack = TRUE,
  sample_folds = 2,
  silent = TRUE)
summary(plm_fit)
```

mdl_glm	<i>Wrapper for <code>stats::glm()</code>.</i>
---------	---

Description

Simple wrapper for `stats::glm()`.

Usage

```
mdl_glm(y, X, ...)
```

Arguments

<code>y</code>	The outcome variable.
<code>X</code>	The feature matrix.
<code>...</code>	Additional arguments passed to <code>glm</code> . See <code>stats::glm()</code> for a complete list of arguments.

Value

`mdl_glm` returns an object of S3 class `mdl_glm` as a simple mask of the return object of `stats::glm()`.

See Also

`stats::glm()`

Other ml_wrapper: `mdl_glmnet()`, `mdl_ranger()`, `mdl_xgboost()`, `ols()`

Examples

```
glm_fit <- mdl_glm(sample(0:1, 100, replace = TRUE),  
                 matrix(rnorm(1000), 100, 10))  
class(glm_fit)
```

mdl_glmnet	<i>Wrapper for <code>glmnet::glmnet()</code>.</i>
------------	---

Description

Simple wrapper for `glmnet::glmnet()` and `glmnet::cv.glmnet()`.

Usage

```
mdl_glmnet(y, X, cv = TRUE, ...)
```

Arguments

y	The outcome variable.
X	The (sparse) feature matrix.
cv	Boolean to indicate use of lasso with cross-validated penalty.
...	Additional arguments passed to <code>glmnet</code> . See <code>glmnet::glmnet()</code> and <code>glmnet::cv.glmnet()</code> for a complete list of arguments.

Value

`mdl_glmnet` returns an object of S3 class `mdl_glmnet` as a simple mask of the return object of `glmnet::glmnet()` or `glmnet::cv.glmnet()`.

References

Friedman J, Hastie T, Tibshirani R (2010). "Regularization Paths for Generalized Linear Models via Coordinate Descent." *Journal of Statistical Software*, 33(1), 1–22.

Simon N, Friedman J, Hastie T, Tibshirani R (2011). "Regularization Paths for Cox's Proportional Hazards Model via Coordinate Descent." *Journal of Statistical Software*, 39(5), 1–13.

See Also

`glmnet::glmnet()`, `glmnet::cv.glmnet()`

Other `ml_wrapper`: `mdl_glm()`, `mdl_ranger()`, `mdl_xgboost()`, `ols()`

Examples

```
glmnet_fit <- mdl_glmnet(rnorm(100), matrix(rnorm(1000), 100, 10))
class(glmnet_fit)
```

<code>mdl_ranger</code>	<i>Wrapper for <code>ranger::ranger()</code>.</i>
-------------------------	---

Description

Simple wrapper for `ranger::ranger()`. Supports regression (default) and probability forests (set `probability = TRUE`).

Usage

```
mdl_ranger(y, X, ...)
```

Arguments

y	The outcome variable.
X	The feature matrix.
...	Additional arguments passed to <code>ranger</code> . See <code>ranger::ranger()</code> for a complete list of arguments.

Value

mdl_ranger returns an object of S3 class ranger as a simple mask of the return object of [ranger::ranger\(\)](#).

References

Wright M N, Ziegler A (2017). "ranger: A fast implementation of random forests for high dimensional data in C++ and R." *Journal of Statistical Software* 77(1), 1-17.

See Also

[ranger::ranger\(\)](#)

Other ml_wrapper: [mdl_glmnet\(\)](#), [mdl_glm\(\)](#), [mdl_xgboost\(\)](#), [ols\(\)](#)

Examples

```
ranger_fit <- mdl_ranger(rnorm(100), matrix(rnorm(1000), 100, 10))
class(ranger_fit)
```

 mdl_xgboost

Wrapper for [xgboost::xgboost\(\)](#).

Description

Simple wrapper for [xgboost::xgboost\(\)](#) with some changes to the default arguments.

Usage

```
mdl_xgboost(y, X, nrounds = 500, verbose = 0, ...)
```

Arguments

y	The outcome variable.
X	The (sparse) feature matrix.
nrounds	max number of boosting iterations.
verbose	If 0, xgboost will stay silent. If 1, it will print information about performance. If 2, some additional information will be printed out. Note that setting verbose > 0 automatically engages the <code>cb.print.evaluation(period=1)</code> callback function.
...	Additional arguments passed to xgboost. See xgboost::xgboost() for a complete list of arguments.

Value

mdl_xgboost returns an object of S3 class mdl_xgboost as a simple mask to the return object of [xgboost::xgboost\(\)](#).

```
print.summary.ddml_ate
```

Print Methods for Treatment Effect Estimators.

Description

Inference methods for treatment effect estimators.

Usage

```
## S3 method for class 'summary.ddml_ate'  
print(x, digits = 3, ...)  
  
## S3 method for class 'summary.ddml_att'  
print(x, digits = 3, ...)  
  
## S3 method for class 'summary.ddml_late'  
print(x, digits = 3, ...)
```

Arguments

x	An object of class <code>summary.ddml_ate</code> , <code>summary.ddml_att</code> , and <code>summary.ddml_late</code> , as returned by <code>summary.ddml_ate()</code> , <code>summary.ddml_att()</code> , and <code>summary.ddml_late()</code> , respectively.
digits	The number of significant digits used for printing.
...	Currently unused.

Value

NULL.

Examples

```
# Construct variables from the included Angrist & Evans (1998) data  
y = AE98[, "worked"]  
D = AE98[, "morekids"]  
X = AE98[, c("age", "agefst", "black", "hisp", "othrace", "educ")]  
  
# Estimate the average treatment effect using a single base learner, ridge.  
ate_fit <- ddml_ate(y, D, X,  
                  learners = list(what = mdl_glmnet,  
                                  args = list(alpha = 0)),  
                  sample_folds = 2,  
                  silent = TRUE)  
  
summary(ate_fit)
```

```
print.summary.ddml_fpliv
```

Print Methods for Treatment Effect Estimators.

Description

Inference methods for treatment effect estimators.

Usage

```
## S3 method for class 'summary.ddml_fpliv'
print(x, digits = 3, ...)
```

```
## S3 method for class 'summary.ddml_pliv'
print(x, digits = 3, ...)
```

```
## S3 method for class 'summary.ddml_plm'
print(x, digits = 3, ...)
```

Arguments

x	An object of class <code>summary.ddml_plm</code> , <code>summary.ddml_pliv</code> , and <code>summary.ddml_fpliv</code> , as returned by <code>summary.ddml_plm()</code> , <code>summary.ddml_pliv()</code> , and <code>summary.ddml_fpliv()</code> , respectively.
digits	Number of significant digits used for printing.
...	Currently unused.

Value

NULL.

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
D = AE98[, "morekids"]
X = AE98[, c("age", "agefst", "black", "hisp", "othrace", "educ")]

# Estimate the partially linear model using a single base learner, ridge.
plm_fit <- ddml_plm(y, D, X,
  learners = list(what = mdl_glmnet,
                 args = list(alpha = 0)),
  sample_folds = 2,
  silent = TRUE)

summary(plm_fit)
```

shortstacking *Predictions using Short-Stacking.*

Description

Predictions using short-stacking.

Usage

```
shortstacking(
  y,
  X,
  Z = NULL,
  learners,
  sample_folds = 2,
  ensemble_type = "average",
  custom_ensemble_weights = NULL,
  compute_insample_predictions = FALSE,
  subsamples = NULL,
  silent = FALSE,
  progress = NULL,
  auxilliary_X = NULL,
  shortstack_y = y
)
```

Arguments

- | | |
|----------|---|
| y | The outcome variable. |
| X | A (sparse) matrix of predictive variables. |
| Z | Optional additional (sparse) matrix of predictive variables. |
| learners | <p>May take one of two forms, depending on whether a single learner or stacking with multiple learners is used for estimation of the predictor. If a single learner is used, learners is a list with two named elements:</p> <ul style="list-style-type: none"> • what The base learner function. The function must be such that it predicts a named input y using a named input X. • args Optional arguments to be passed to what. <p>If stacking with multiple learners is used, learners is a list of lists, each containing four named elements:</p> <ul style="list-style-type: none"> • fun The base learner function. The function must be such that it predicts a named input y using a named input X. • args Optional arguments to be passed to fun. • assign_X An optional vector of column indices corresponding to predictive variables in X that are passed to the base learner. • assign_Z An optional vector of column indices corresponding to predictive in Z that are passed to the base learner. |

Omission of the `args` element results in default arguments being used in `fun`. Omission of `assign_X` (and/or `assign_Z`) results in inclusion of all variables in `X` (and/or `Z`).

<code>sample_folds</code>	Number of cross-fitting folds.
<code>ensemble_type</code>	Ensemble method to combine base learners into final estimate of the conditional expectation functions. Possible values are: <ul style="list-style-type: none"> • "nnls" Non-negative least squares. • "nnls1" Non-negative least squares with the constraint that all weights sum to one. • "singlebest" Select base learner with minimum MSPE. • "ols" Ordinary least squares. • "average" Simple average over base learners. Multiple ensemble types may be passed as a vector of strings.
<code>custom_ensemble_weights</code>	A numerical matrix with user-specified ensemble weights. Each column corresponds to a custom ensemble specification, each row corresponds to a base learner in <code>learners</code> (in chronological order). Optional column names are used to name the estimation results corresponding the custom ensemble specification.
<code>compute_insample_predictions</code>	Indicator equal to 1 if in-sample predictions should also be computed.
<code>subsamples</code>	List of vectors with sample indices for cross-fitting.
<code>silent</code>	Boolean to silence estimation updates.
<code>progress</code>	String to print before learner and cv fold progress.
<code>auxilliary_X</code>	An optional list of matrices of length <code>sample_folds</code> , each containing additional observations to calculate predictions for.
<code>shortstack_y</code>	Optional vector of the outcome variable to form short-stacking predictions for. Base learners are always trained on <code>y</code> .

Value

`shortstack` returns a list containing the following components:

<code>oos_fitted</code>	A matrix of out-of-sample predictions, each column corresponding to an ensemble type (in chronological order).
<code>weights</code>	An array, providing the weight assigned to each base learner (in chronological order) by the ensemble procedures.
<code>is_fitted</code>	When <code>compute_insample_predictions = T</code> , a list of matrices with in-sample predictions by sample fold.
<code>auxilliary_fitted</code>	When <code>auxilliary_X</code> is not <code>NULL</code> , a list of matrices with additional predictions.
<code>oos_fitted_bylearner</code>	A matrix of out-of-sample predictions, each column corresponding to a base learner (in chronological order).
<code>is_fitted_bylearner</code>	When <code>compute_insample_predictions = T</code> , a list of matrices with in-sample predictions by sample fold.

auxilliary_fitted_bylearner When auxilliary_X is not NULL, a list of matrices with additional predictions for each learner.

Note that unlike crosspred, shortstack always computes out-of-sample predictions for each base learner (at no additional computational cost).

References

Ahrens A, Hansen C B, Schaffer M E, Wiemann T (2023). "ddml: Double/debiased machine learning in Stata." <https://arxiv.org/abs/2301.09397>

Wolpert D H (1992). "Stacked generalization." Neural Networks, 5(2), 241-259.

See Also

Other utilities: [crosspred\(\)](#), [crossval\(\)](#)

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
X = AE98[, c("morekids", "age", "agefst", "black", "hispanic", "othrace", "educ")]

# Compute predictions using shortstacking with base learners ols and lasso.
# Two stacking approaches are simultaneously computed: Equally
# weighted (ensemble_type = "average") and MSPE-minimizing with weights
# in the unit simplex (ensemble_type = "nnls1"). Predictions for each
# learner are also calculated.
shortstack_res <- shortstacking(y, X,
                               learners = list(list(fun = ols),
                                                list(fun = mdl_glmnet)),
                               ensemble_type = c("average",
                                                "nnls1",
                                                "singlebest"),
                               sample_folds = 2,
                               silent = TRUE)
dim(shortstack_res$oos_fitted) # = length(y) by length(ensemble_type)
dim(shortstack_res$oos_fitted_bylearner) # = length(y) by length(learners)
```

Description

Inference methods for treatment effect estimators.

Usage

```
## S3 method for class 'ddml_ate'
summary(object, ...)

## S3 method for class 'ddml_att'
summary(object, ...)

## S3 method for class 'ddml_late'
summary(object, ...)
```

Arguments

object An object of class ddml_ate, ddml_att, and ddml_late, as fitted by `ddml_ate()`, `ddml_att()`, and `ddml_late()`, respectively.

... Currently unused.

Value

A matrix with inference results.

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
D = AE98[, "morekids"]
X = AE98[, c("age", "agefst", "black", "hisp", "othrace", "educ")]

# Estimate the average treatment effect using a single base learner, ridge.
ate_fit <- ddml_ate(y, D, X,
  learners = list(what = mdl_glmnet,
    args = list(alpha = 0)),
  sample_folds = 2,
  silent = TRUE)

summary(ate_fit)
```

summary.ddml_fpliv *Inference Methods for Partially Linear Estimators.*

Description

Inference methods for partially linear estimators. Simple wrapper for `sandwich::vcovHC()`.

Usage

```
## S3 method for class 'ddml_fpliv'
summary(object, ...)

## S3 method for class 'ddml_pliv'
```

```
summary(object, ...)

## S3 method for class 'ddml_plm'
summary(object, ...)
```

Arguments

object An object of class `ddml_plm`, `ddml_pliv`, or `ddml_fpliv` as fitted by `ddml_plm()`, `ddml_pliv()`, and `ddml_fpliv()`, respectively.

... Additional arguments passed to `vcovHC`. See `sandwich::vcovHC()` for a complete list of arguments.

Value

An array with inference results for each `ensemble_type`.

References

Zeileis A (2004). "Econometric Computing with HC and HAC Covariance Matrix Estimators." *Journal of Statistical Software*, 11(10), 1-17.

Zeileis A (2006). "Object-Oriented Computation of Sandwich Estimators." *Journal of Statistical Software*, 16(9), 1-16.

Zeileis A, Köll S, Graham N (2020). "Various Versatile Variances: An Object-Oriented Implementation of Clustered Covariances in R." *Journal of Statistical Software*, 95(1), 1-36.

See Also

[sandwich::vcovHC\(\)](#)

Examples

```
# Construct variables from the included Angrist & Evans (1998) data
y = AE98[, "worked"]
D = AE98[, "morekids"]
X = AE98[, c("age", "agefst", "black", "hisp", "othrace", "educ")]

# Estimate the partially linear model using a single base learner, ridge.
plm_fit <- ddml_plm(y, D, X,
  learners = list(what = mdl_glmnet,
                 args = list(alpha = 0)),
  sample_folds = 2,
  silent = TRUE)

summary(plm_fit)
```

Index

- * **datasets**
 - AE98, 2
- * **ddml**
 - ddml_ate, 8
 - ddml_fpliv, 12
 - ddml_late, 15
 - ddml_pliv, 18
 - ddml_plm, 21
- * **ml_wrapper**
 - mdl_glm, 25
 - mdl_glmnet, 25
 - mdl_ranger, 26
 - mdl_xgboost, 27
 - ols, 28
- * **utilities**
 - crosspred, 3
 - crossval, 6
 - shortstacking, 31

AE98, 2
AER::ivreg(), 14, 21

crosspred, 3, 7, 33
crossval, 5, 6, 33

ddml, 7
ddml_ate, 8, 14, 18, 21, 24
ddml_ate(), 34
ddml_att(ddml_ate), 8
ddml_att(), 34
ddml_fpliv, 11, 12, 18, 21, 24
ddml_fpliv(), 35
ddml_late, 11, 14, 15, 21, 24
ddml_late(), 34
ddml_pliv, 11, 14, 18, 18, 24
ddml_pliv(), 35
ddml_plm, 11, 14, 18, 21, 21
ddml_plm(), 35

glmnet::cv.glmnet(), 25, 26

glmnet::glmnet(), 25, 26

mdl_glm, 25, 26–28
mdl_glmnet, 25, 25, 27, 28
mdl_ranger, 25, 26, 26, 28
mdl_xgboost, 25–27, 27, 28

ols, 25–28, 28

print.summary.ddml_ate, 29
print.summary.ddml_att
(print.summary.ddml_ate), 29
print.summary.ddml_fpliv, 30
print.summary.ddml_late
(print.summary.ddml_ate), 29
print.summary.ddml_pliv
(print.summary.ddml_fpliv), 30
print.summary.ddml_plm
(print.summary.ddml_fpliv), 30

ranger::ranger(), 26, 27

sandwich::vcovHC(), 34, 35
shortstacking, 5, 7, 31
stats::glm(), 25
summary.ddml_ate, 33
summary.ddml_ate(), 10, 11, 29
summary.ddml_att(summary.ddml_ate), 33
summary.ddml_att(), 10, 11, 29
summary.ddml_fpliv, 34
summary.ddml_fpliv(), 14, 30
summary.ddml_late(summary.ddml_ate), 33
summary.ddml_late(), 17, 18, 29
summary.ddml_pliv(summary.ddml_fpliv),
34
summary.ddml_pliv(), 21, 30
summary.ddml_plm(summary.ddml_fpliv),
34
summary.ddml_plm(), 24, 30

xgboost::xgboost(), 27, 28